CUI DEVICES

SERIES: ACZ11 | **DESCRIPTION:** MECHANICAL INCREMENTAL ENCODER

ELECTRICAL SPECIFICATIONS

parameter	conditions/description
output waveform	square wave
output signals	A, B phase
current consumption	10 mA
output phase difference	T1, T2, T3, T4 ≥ 3.5 ms @ 60 rpm (see output waveform)
supply voltage	5 V dc max.
output resolution	12, 15, 20, 30 ppr
switch rating	12 V dc, 50 mA (ACZ11BRXE models only)
insulation resistance	300 V dc, 100 MΩ
withstand voltage	300 V ac

MECHANICAL SPECIFICATIONS

parameter	conditions/description	min	nom	max	units
shaft load	axial			8	kgf
rotational torque	with detent click without detent click	60 60	140 80	220 100	gf•cm gf•cm
push switch operational force	(ACZ11BRXE models only)	300		900	gf•cm
push switch life	(ACZ11BRXE models only)			50,000	cycles
rotational life				30,000	cycles

ENVIRONMENTAL SPECIFICATIONS

parameter	conditions/description	min	nom	max	units
operating temperature		-10		65	°C
storage temperature		-40		75	°C
humidity		85			% RH
vibration	0.75 mm max. travel for 2 hours	10		55	Hz

PART NUMBER KEY

ACZ11 X BR X E- XX XX X1- XXX

Version:
"blank" = switch (momentary)
N = no switch

Bushing:
1 = M7 x 0.75 (H = 5)
2 = M7 x 0.75 (H = 7)
4 = smooth (H = 5)
5 = smooth (H = 7)


Shaft length:
15, 20, 25

Shaft type:
KQ, S, F

Mounting orientation:
A = Horizontal
D = Vertical

Resolution (ppr):
12 = 12 ppr, no detent
12C = 12 ppr, 12 detent
15 = 15 ppr, no detent
30C15P = 15 ppr, 30 detent
20 = 20 ppr, no detent
20C = 20 ppr, 20 detent
30 = 30 ppr, no detent
30C = 30 ppr, 30 detent

SHAFT OPTIONS



switch travel for ACZ11BRXE only

BUSHING

	Condition	H
1	M7-P0.7 5	5
2	M7-P0.7 5	7
4	smooth	5
5	smooth	7

H=5

	15KQ	20KQ	25K Q
L	15	20	25
I	7	10	12

H=7

	15KQ	20KQ	25K Q
L	15	20	25
I	5	8.5	10

H=5

	15S	20S	25S
L	15	20	25

H=7

	15S	20S	25S
L	15	20	25


H=5

	15F	20F	25F
L	15	20	25
F	8	12	12

H=7


	15F	20F	25F
L	15	20	25
F	8	12	12

OUTPUT WAVEFORM



CW direction (@ 60 rpm)

DETENT POSITIONS




CW direction →


CW direction →

SLIDING NOISE

t = Masking time to avoid chatter (5mS) $V_1 = V_2 = 1V$ max.




SUGGESTED FILTER




R1, R2, R3, R4 = 10kΩ
C1, C2 = 0.01µF

MECHANICAL DRAWING (horizontal)

ACZ11NBRXE




ACZ11BRXE




MECHANICAL DRAWING (vertical)

ACZ11NBRXE



ACZ11BRXE



REVISION HISTORY

rev.	description	date
1.0	initial release	10/30/2009
1.01	brand update	10/04/2019
1.02	updated datasheet	06/15/2020

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

cuidevices.com

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Same Sky:

SR5-3V-200-1C CDM809-08A-FW-F010-050-67 SP-3540 CFM-5015V-150-290 MPB02-1C54-R-CAP-R-D PPM-2-5525-SG-WT SR7-12V-200-1C CFM-4020V-145-123 PR6-12V-450-1A PR6-5V-450-1A CFM-4020BF-095-342-20 CMI-9653S-SMT-TR PJ-002A CT-1205C-SMT-TR TB007-508-03BE TB007-508-02BE UJ20-C-H-G-SMT-TR TBL007A-500-02GY CFM-6015V-239-292-20 TBP02R2-381-12BE C14D16P-B3 SJ-3552B-MSMT-TR-67 MPB01-1C54-SB-CAP-BK-D CUSP-R80-18-2400-TH CMT-85853-97-SMT-TR CBM-A232B-230-521-20 SJ-63053A HSE-B20250-045H CFM-A225B-018-327-20 TS02-66-90-BK-260-LCR-D