Data Sheet

HUBER+SUHNER

Within Series Adaptor
32_MMBX-50-0-13/111_N

Description

Adaptor plug/plug
MMBX plug (male) / MMBX plug (male)

Slide - snap interface

Interface standard
Series MMBX - SUHNER-MMBX



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	12.4 GHz		
Frequency range	DC to 2.5 GHz	2.5 to 6 GHz	6 to 12.4 GHz
Return loss	≥ 32 dB	≥ 26 dB	≥ 15 dB

Mechanical Data

Number of matings	100
Weight	0.0004 kg

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Interface - MMBX plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Body	Bronze	SUCOPRO Plating
Insulator	PFA / PTFE	

Interface - MMBX plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze	SUCOPRO Plating
Body	Bronze	SUCOPRO Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00064707

Ordering Information

Single package	32_MMBX-50-0-13/111_NE
Bulk 100 pcs package	32_MMBX-50-0-13/111_NH
Tray package	32_MMBX-50-0-13/111_NY

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

23002145 33_PC24-SK-50-2/199_NE MINIBEND R-12 RG_196_A/U 11_TNC-50-3-116/133_NE 12012090
22511964 MINIBEND R-10 11MMBXEF31616MMBX/300 1399.17.0210 6601_PC185-50-1/199_NE
16_MMCX-50-2-4/111_OH G032D/Nm/SMAm/1000 1399.31.0020 24_SMA-50-2-15/111_NH 6806.19.A
84093961 84118385 G032D/BNCm/BNCm/1000 Minibend L-10 PCRS_LCMX_LCMX_O421T_30.0_LL
12535682 23000457 85201112 MINIBEND R-8 RADOX 125 0.75 MMÂ² RED 6620_SMA-50-2/199_NE
G_03130_HT-01 11_SMC-50-2-10/111_NE 1399.17.0231