# Data Sheet

HUBER+SUHNER

## Coaxial Cable Connector
## 21_N-75-4-8/133_N

## Description

Straight cable jack

Interface standards
IEC 60169-16_MIL-STD-348A/304_CECC 22210



## Technical Data

### Electrical Data

| | |
|---|---|
| Impedance | 75 Ω |
| Interface frequency max. | 1.5 GHz |

### Mechanical Data

| | |
|---|---|
| Centre contact | crimped |
| Outer contact | crimped |
| Weight | 0.0333 kg |

### Environmental Data

| | |
|---|---|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

### Material Data

| Piece Parts | Material | Surface Plating |
|---|---|---|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |
| Crimp ferrule | Copper | SUCOPLATE (R) Plating |

## Related Documents

| | |
|---|---|
| Catalogue drawing | DOU-00006318 |
| Assembly instruction | DOC-0000179851 |

## Ordering Information

| | |
|---|---|
| Single package | 21_N-75-4-8/133_NE |

## Additional Information

| | |
|---|---|
| Suitable cables | RG_59_B/U, GX_04273 |



Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## Huber+Suhner:

Minibend L-10 G_03130_HT-01 MINIBEND R-10 PCRS_LCMX_LCMX_O421T_30.0_LL RADOX 125 0.75 MMÂ² RED 11MMBXEF31616MMBX/300 11_SMC-50-2-10/111_NE 23000457 24_SMA-50-2-15/111_NH 33_PC24-SK-50-2/199_NE 6601_PC185-50-1/199_NE MINIBEND R-8 11_TNC-50-3-116/133_NE 12535682 6620_SMA-50-2/199_NE 84093961 84118385 16_MMCX-50-2-4/111_OH 22511964 6806.19.A MINIBEND R-12 RG_196_A/U 12012090 G032D/BNCm/BNCm/1000 1399.31.0020 23002145 G032D/Nm/SMAm/1000 1399.17.0210 1399.17.0231 85201112