74LVC1G17 Single Schmitt-Trigger Buffer

1. General Description

1.1 Description

This single Schmitt-trigger buffer is designed for 1.65-V to 5.5-V VCC operation.

The 74LVC1G17 device contains one buffer and performs the Boolean function Y = A.

The CMOS device has high output drive while maintaining low static power dissipation over a broad Vcc operating range.

1.2 Features

- Supports 5V V_{CC} operation
- Inputs accept voltages to 5.5V
- Provides down translation to V_{CC}
- Low power consumption, 10μA max I_{CC}
- ±24mA output drive at 3.3V
- I_{off} supports live insertion, partial-power-down mode, and back-drive protection

1.3 Device Information

PART NUMBER	PACKAGE
74LVC1G17	SOT23
	SC70
	SOT5X3
	DFN
	DSBGA

2. Connection Diagrams and Pin Description




Figure 2.1 Top View

PIN No.				NAME	I/O	FUNCTION
LT/CT/DT	BD/CD	ED	AG			
1	1,5	1	--	NC		No Connected
2	2	2	2	A	I	Input
3	3	3	3	GND		Ground
4	4	4	4	Y	O	Output
5	6	5	5	VCC		Supply Voltage

3. System Diagram

3.1 Logic Diagram



Figure 3.1：74LVC1G17 Logic Diagram

3.2 Function Table

Input	Output
A	Y
1	1
0	0

X = don’t care, 1≡High State, 0≡Low State,Z=High Impedance

4. Specifications

4.1 Absolute Maximum Ratings

Symbol	Parameter	MIN	MAX	Unit
V_{CC}	Supply Voltage	-0.5	6.5	V
V_I	Input Voltage Range	-0.5	6.5	V
V_O	Voltage Range(applied to any output in the high-impedance or power-off state)(1)	-0.5	6.5	V
	Voltage Range(applied to any output in the high or low state)	-0.5	VCC + 0.5	V
I_O	Continuous Output Current		±50	mA
T_J	Junction Temperature		125	℃
T_{OP}	Operating Temperature	-40	85	℃

Absolute maximum ratings are those values beyond which the device could be permanently damaged,These are stress ratings only,which do not imply functional operation of the device at these or any other conditions beyond those indicated under normal operating conditions.

4.2 Electrical Characteristics

4.2.1 DC Specifications

(T_a=25℃, voltages are referenced to GND (ground=0V), unless otherwise specified)

Symbol	Parameter	Test Condition	MIN	TYP	MAX	Unit
I_{OH}	High Level Output Current	V_{CC}=1.65V	--	--	-4	mA
		V_{CC}=2.3V	--	--	-8	mA
		V_{CC}=3V	--	--	-16	mA
			--	--	-24	mA
		V_{CC}=4.5V	--	--	-32	mA
I_{OL}	Low Level Output Current	V_{CC}=1.65V	--	--	4	mA
		V_{CC}=2.3V	--	--	8	mA
		V_{CC}=3V	--	--	16	mA
			--	--	24	mA
		V_{CC}=4.5V	--	--	32	mA

Symbol	Parameter	Test Condition	MIN	TYP	MAX	Unit
V_{T+}	(Positive-going input threshold voltage)	V_{CC}=1.65V	0.76	--	1.13	V
		V_{CC}=2.3V	1.08	--	1.56	V
		V_{CC}=3V	1.48	--	1.92	V
		V_{CC}=4.5V	2.19	--	2.74	V
		V_{CC}=5.5V	2.65	--	3.33	
V_{T-}	(Negative-going input threshold voltage)	V_{CC}=1.65	0.38	--	0.62	V
		V_{CC}=2.3V	0.59	--	0.91	V
		V_{CC}=3V	0.85	--	1.15	V
		V_{CC}=4.5V	1.35	--	1.85	V
		V_{CC}=5.5V	1.75		2.25	V
ΔV_T	ΔV_T Hysteresis (V_{T+} – V_{T-})	V_{CC}=1.65V	0.35	--	0.65	V
		V_{CC}=2.3V	0.45	--	0.8	V
		V_{CC}=3V	0.5	--	0.9	V
		V_{CC}=4.5V	0.65	--	1.05	V
		V_{CC}=5.5V	0.8	--	1.2	V
V_{OH}	High Level Output Voltage	V_{CC}=1.65V to 5.5V,I_{OH}=-100uA	V_{CC}-0.1	--	--	V
		V_{CC}=1.65V,I_O=-4mA	--	1.47	--	V
		V_{CC}=2.3V,I_O=-8mA	--	2.15	--	V
		V_{CC}=3V,I_O=-16mA	--	2.8	--	V
		V_{CC}=3V,I_O=-24mA	--	2.7	--	V
		V_{CC}=4.5V,I_O=-32mA	--	4.2	--	V
V_{OL}	Low Level Output Voltage	V_{CC}=1.65V to 5.5V,I_{OH}=100uA	--	--	0.1	V
		V_{CC}=1.65V,I_O=4mA	--	0.09	--	V
		V_{CC}=2.3V,I_O=8mA	--	0.1	--	V
		V_{CC}=3V,I_O=16mA	--	0.15	--	V
		V_{CC}=3V,I_O=24mA	--	0.25	--	V
		V_{CC}=4.5V,I_O=32mA	--	0.25	--	V
I_I	A Inputs Leakage Current	V_{CC}=0 to 5.5V,V_I=V_{CC} or GND	--	0	±1	uA
I_{off}	Power Off Leakage Current	V_{CC}=0V,V_I or V_O=5.5V	--	0	±10	uA
I_{CC}	Quiescent Supply Current	V_{CC}=1.65V to 5.5V,V_I=V_{CC} or GND,I_O=0	--	0	10	uA
ΔI_{CC}	Additional Quiescent Supply Current Per Input Pin	V_{CC}=3V to 5.5V,one input at V_{CC} -0.6V,Other inputs at V_{CC} or GND	--	0	500	uA

5. Application Information





Figure 5.1：Application Schematic

6. Ordering Information

Orderable Device	Package Type	Pins	Packing	Package Qty
74LVC1G17LT05ARCQ	SOT23	5	Tape & Reel	3000
74LVC1G17CT05ARCQ	SC70	5	Tape & Reel	3000
74LVC1G17DT05ARDQ	SOT5x3	5	Tape & Reel	4000
74LVC1G17BD06AREQ	DFN(BD)	6	Tape & Reel	5000
74LVC1G17CD06AREQ	DFN(CD)	6	Tape & Reel	5000
74LVC1G17ED05ARCQ	DFN	5	Tape & Reel	3000
74LVC1G17AG05ARCQ	DSBGA	5	Tape & Reel	3000


7. Package Information

7.1 SOT23-5




Symbol	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.90	-	1.45	0.035	-	0.057
A1	-	-	0.15	-	-	0.006
A2	0.90	-	1.30	0.035	-	0.051
b	0.35	-	0.50	0.014	-	0.020
c	0.09	-	0.20	0.004	-	0.008
D	2.80	-	3.05	0.110	-	0.120
E	1.50	-	1.75	0.059	-	0.069
e	-	0.95	-	-	0.037	-
H	2.60	-	3.00	0.102	-	0.118
L	0.10	-	0.60	0.004	-	0.024
θ	0 degrees	-	10 degrees	-	-	-

7.2 SC70




Symbol	Dim in mm		
	MIN	TYP	MAX
A	0.90	1.00	1.10
A1	0.00	0.05	0.10
A2	0.90	0.95	1.00
b	0.15	0.25	0.35
C	0.10	0.12	0.15
D	1.80	2.00	2.20
E	2.15	2.25	2.35
E1	1.15	1.25	1.35
e	0.650TYP.		
el	1.20	1.30	1.40
L	0.25	0.30	0.40
L2	0.15TYP.		
Y	0.00	0.05	0.10
θ	4°	8°	12°


7.3 SOT5X3


1.7
1.5
PIN 1
ID AREA
A
1
5
2X 0.5
2X 1
1.7
1.5
NOTE 3
3
4
B
1.3
1.1
5X 0.3
0.1
0.05
0.00 TYP
0.6 MAX
C
SEATING PLANE
5X 0.18
0.08
0.05 C
SYMM
SYMM
5X 0.27
0.15
5X 0.4
0.2
0.1 M C A B
0.05 M C
ALTERNATIVE PACKAGE
SINGULATION VIEW


7.4 DFN(BD)-6


B
1.05
0.95
A
PIN 1 INDEX AREA
1.5
1.4
0.6 MAX
C
SEATING PLANE
0.05
0.00
0.08 C
3X 0.6
SYMM
(0.05) TYP
3
4
4X
0.5
SYMM
2X
1
1
6
6X 0.25
0.15
0.1 M C A B
0.05 M C
0.4
0.3
PIN 1 ID
(OPTIONAL)
5X 0.35
0.25
(0.127) TYP


7.5 DFN(CD)-6



B
1.05
0.95
A
PIN 1 INDEX AREA
1.05
0.95
0.4 MAX
C
SEATING PLANE
0.05 C
SYMM
(0.11) TYP
0.05
0.00
3
4
SYMM
2X
0.7
4X
0.35
1
6
6X 0.22
0.12
(0.1)
PIN 1 ID
6X 0.45
0.35
0.07 M C B A
0.05 M C


7.6 DFN5


B
0.85
0.75
A
PIN 1 INDEX AREA
0.85
0.75
0.4 MAX
C
SEATING PLANE
NOTE 3
4X (0.05)
(0.324)
0.25±0.1
2
2X
0.48
1
3
4
2X (0.26)
5
0.239
0.139
3X 0.288
0.188
4X 0.27
0.17
0.1 M C A B
0.05 M C
(0.1)
0.05
0.00
NOTE 3

7.7 DSBGA







D: Max = 1.418 mm, Min =1.358 mm

E: Max = 0.918 mm, Min =0.858 mm