




RoHS

















适用线路板(PCB LAYOUT)

Model No.	Pin	A	B	C
WAFER-TJC8-2.54-2PWZ	2	2.54	7.50	5.60
WAFER-TJC8-2.54-4PWZ	4	10.99	15.95	14.05
WAFER-TJC8-2.54-6PWZ	6	19.44	24.40	22.50
WAFER-TJC8-2.54-8PWZ	8	27.89	32.85	30.95
WAFER-TJC8-2.54-10PWZ	10	36.34	41.30	39.40
WAFER-TJC8-2.54-12PWZ	12	44.79	49.75	47.85

Specifications/技术规格:

1.Poles/线数：2P、4P、6P、8P、10P、12P
2.Wire range/适用线规：AGW 26#～22#
3.Applicable PC board thickness/ 适用PC板厚度：1.6mm
4.Current rating/额定电流：3.0A
5.Voltage rating/额定电压：250V DC/AC
6.Insulation Resistance/ 绝缘电阻：1000MΩ Min
7.Dielectric Withstanding/ 耐电压：1500V AC/minute
8.Contact Resistance/ 接触电阻：20mΩ Max
9.Operating Temperature/ 工作温度：-25℃ to +85℃

NO.	Name	Number	Qty	Materil	Remarks
Ⓑ	Terminal			Brass	Plating Sn
Ⓐ	Housing		1	PA66	Black

Zhongdi Electronic Technology Co., Ltd

								angle	±2°		design		date		name	WAFER CONNECTOR
								10~30	±0.30		Review		date			
								5~10	±0.20		Approved		date		model	WAFER-TJC8-2.54-□□PWZ
								~ 5	±0.10	Drawing number:						
				modify		Review	Approved	Tolerance not specified		Proportion	1:1	unit	mm	gape number		A4

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ZHONGDI:

WAFER-VH3.96-5PWT-W1-P WAFER-HY2.0-6PLT-W1-P WAFER-PH2.0-2PWT-W1-P
WAFER-SHB1.0-13PLT-W1-P WAFER-TJC8-2.54-2PWZ WAFER-GH1.25-14PWT-W1-P
WAFER-MX1.25-2PWZ-C22-9T WAFER-MX1.25-5PZZ-C22-9T WAFER-SH1.0-11PLT-W1-P
WAFER-SH1.0-8PWT-W1-P WAFER-SUR0.8-14PWT-W1-P WAFER-XHB2.54-7PWT-W1-P
WAFER-MX1.25-4PWZ-C22-9T WAFER-ZH1.5-2PLT-W1-P WAFER-ZH1.5-4PLT-W1-P
WAFER-XH2.54-12PWT-W1-P WAFER-GH1.25-12PLT-W1-P WAFER-HY2.0-4PWT-W1-P
WAFER-SH1.0-6PWT-W1-P WAFER-SUR0.8-12PWT-W1-P WAFER-SUR0.8-4PLT-W1-P
WAFER-TJC8-2.54-12PZZ WAFER-HY2.0-10PWT-W1-P WAFER-HY2.0-6PWT-W1-P
WAFER-HY2.0-7PWT-W1-P WAFER-MX1.25-5PLT-W1-P WAFER-SHB1.0-8PWT-W1-P
WAFER-VH3.96-3PWT-W1-P WAFER-ZH1.5-12PWT-W1-P WAFER-ZH1.5-2PWT-W1-P