Data Sheet

Coaxial Cable Connector
24_SMB-50-2-13/111_N

Description

Straight bulkhead cable feed through

Interface standards
IEC 60169-10_MIL-STD-348A/311_CECC 22130



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0018 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)

Related Documents

Outline drawing	DOU-00009688
Catalogue drawing	DCA-00009690
Assembly instruction	DOC-0000179074
Mounting hole	DOU-00008855

Ordering Information

Single package	24_SMB-50-2-13/111_NE
Bulk 100 pcs package	24_SMB-50-2-13/111_NH

Additional Information

Suitable cables	EZ_86_TP_M17, SUCOFORM_86, MULTIFLEX_86

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000186493 Q / PDO E / date of publication: 10.05.2017 18:40:04 / uncontrolled copy

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

24_SMB-50-2-13/111_NH 24_SMB-50-2-13/111_NE