
216RS4

Wall mounted socket

2CMA193097R1000



Wall mounted socket, earthing sleeve position 4h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Yellow

GENERAL

Product Name	Wall mounted socket
Product ID	2CMA193097R1000
Function	Wall mounted socket
EAN	739269699
Catalog Description	Surface socket-outlet, 4h, 16A, IP44, 2P+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2420031
E-Number Norway	1542301
E-Number Sweden	E2416442
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	ERS
Color	Yellow
Number of Poles	3
Clock Position	4Hour
Rated Current	16 ampere
Rated Voltage	100 ... 130 volt
Frequency	50 hertz|60 hertz
Degree of Protection	IP44
Cable Cross-Section	1.5...4 mm²
Housing Material	Plastic (PA)
Plug Angle	
Product Group	Easy&Safe

DIMENSIONS

Product Net Width	66 millimetre
Product Net Height	91 millimetre
Product Net Length	117 millimetre
Product Net Depth	117 millimetre
Product Net Weight	0.22 kilogram

PACKAGING

Package Width	138 millimetre
Package Height	345 millimetre
Package Gross Weight	2.2 kilogram
Package Length	158 millimetre
Package Units	box 10 piece

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

65781-158 68001-108HLF 68001-200HLF 70430-164LF 76384-316LF 54202-G0805CLF 86093968813H45V1LF 91614-403ALF 70234-112LF 95157-140LF 70218-1116LF 86130202123355E1LF DEM09P032N 54202-S08-07LF 67996-204HLF 68002116HLF 86093488314745V1LF CD15S13E4RV09LF DCMF37P RJSBE5080C2 69192-408HLF 86093968191755E3LF 863013A D15P13A6RV12LF 68000-236HLF 86093967896755LF DAPO15S365TLF LD15P33E4GV00LF LD25S33E4GV00LF RJE061661210