332RU6

Panel mounted socket

2CMA193250R1000



Panel mounted socket, earthing sleeve position 6h, rated current 32A, IP44 splashproof, unified flange, straight, 3-poles+earth, frequency 50-60 Hz, color code Red

GENERAL

Product Name	Panel mounted socket
Product ID	2CMA193250R1000
Function	Panel mounted socket
EAN	73926969329
Catalog Description	Socket-outlet, panel mounting, 6h, 32A, IP44, unified flange, straight, 3P+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2421243
E-Number Norway	1547343
E-Number Sweden	E2416657
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	ERU
Color	Red
Number of Poles	4
Clock Position	6Hour
Rated Current	32 ampere
Rated Voltage	380 ... 415 volt
Frequency	50 hertz|60 hertz
Degree of Protection	IP44
Cable Cross-Section	2.5...10 mm²
Housing Material	Plastic (PA)
Plug Angle	Straight
Product Group	Easy&Safe

DIMENSIONS

Product Net Width	75 millimetre
Product Net Height	100 millimetre
Product Net Length	103 millimetre
Product Net Depth	103 millimetre
Product Net Weight	0.26 kilogram

PACKAGING

Package Width	154 millimetre
Package Height	378 millimetre
Package Gross Weight	2.6 kilogram
Package Length	182 millimetre
Package Units	box 10 piece

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

86093488314745V1LF 95157-140LF 68001-200HLF 86093968813H45V1LF 86130202123355E1LF
91614-403ALF D15P13A6RV12LF LD15P33E4GV00LF 70234-112LF DEM09P032N 70430-164LF
DAPO15S365TLF RJSBE5080C2 68001-108HLF 68002116HLF 65781-158 863013A RJE061661210
54202-G0805CLF 54202-S08-07LF 76384-316LF CD15S13E4RV09LF LD25S33E4GV00LF 67996-204HLF
68000-236HLF 69192-408HLF 70218-1116LF 86093967896755LF 86093968191755E3LF DCMF37P