


ROHS Compliant


MAPX	MODIFICATION	DATE	DRAW	APPROVE









RECOMMEND PULG








PCB.WELDING DRAWING (TOLERANCE:±0.05)

Main technical performance	
Rated electrical load	DC 12V 2A
Contact resistance	≤0.03Ω
Insulation resistance	≥100MΩ DC250V
Pressure resistance	AC 500V 1min
Insertion force	3-30N
Operating temperature range	-20C°~+70C°
service life	5000cycles



SCHEMATIC

4	TERMINAL	1	BRASS	MB:CuSn PLATED
3	HOUSING	1	PPA	BLACK
2	TIP SPRING	1	PHOSPHOR BRONZE	MB:CuSn PLATED
1	CENTER PIN	1	BRASS	MB:CuSn PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

MANUFACTURE DWG

东莞市讯普电子科技有限公司
DongGuan XunPu Electronics Co,Ltd

UNLESS OTHERWISE SPECIFED TOLERANCES

DECIMALS:	ANGLES:
X.X±0.30	X.°±5°
X.XX±0.25	X.X°±1°
X.XXX±0.15	


CUSTOMER COPY


TITLE: DC SOCKET


PAR	DC-045B-B130	
DWN		
CHKD		
APVD		
SCALE N:A	UNIT:MM	
SIZE:A4	SHEET:1F1	REV:A


ROHS Compliant

MAPX	MODIFICATION	DATE	DRAW	APPROVE












Pull Out Direction



Pull Out Direction



NOTES :
1. CARTON SPEC. :350 *350 *350mm(OUT DIM) , PAPPER THICKNESS =5mm
2. UPPER and DOWN EPS: 350*350mm THICKNESS =8mm.
3. THE COVER TAPE PEELING FORCE:30~100g.
4. PER REEL CASED ONE AIR BLADDER BAG.
5. CARRIER TAPE COLOR:BLACK.



MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co,Ltd			
UNLESS OTHERWISE SPECIFED TOLERANCES			TITLE: DC SOCKET		
			PAR	DC-045B-B130	
DECIMALS:	ANGLES:		DWN		
.X:±0.30	.X°:±5°		CHKD		
.XX:±0.20	.XX°:±3°		APVD		
.XXX:±0.10	.XXX°:±1°	CUSTOMER COPY	SCALE1:1	UNIT:MM	
			SIZE:A4	SHEET:1F1	REV:A

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

XUNPU:

FPC-0.5FX-14PWCR-H20 SMA-KWE-323C-H13X23-LW WAFER-MX1.25B-8PWB FPC-0.5FX-20PWBH15 FPC-0.5FX-4PWBH15 FPC-1.0AX-14PWCR-H25 TYPEC-304YDSW-ACP16 WAFER-GH1.25-6PLB RJ45-005-014-11 WAFER-PH2.0-3PWB WAFER-PH2.0-8PLB FPC-0.5AL-6PB FPC-0.5FX-16PWCR-H20 WAFER-VH3.96-4PLB FPC-0.5AX-30PWCR-H20 FPC-0.5HF-10PWBR-H20 FPC-1.0AX-4PWCR-H25 HDMI-212L PHB2.0-02-20PZZ FPC-0.5AX-24PWCR-H20 FPC-0.5FX-4PWCR-H20 MU-103-ARW64 WAFER-PH2.0-2PJK WAFER-PH2.0-6PWB WAFER-WBM4.2-16PJK-GB FPC-1.0HF-4PWAR-H20 WAFER-PH2.0-11PZZ WAFER-XH2.54-4PWZ-H62 DC-031A-A100 FPC-0.5AS-5PWCR-H20