432BS6W

Wall mounted inlet

2CMA167122R1000



Surface Inlet, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

GENERAL

Product Name	Wall mounted inlet
Product ID	2CMA167122R1000
Function	Surface inlet
EAN	7392696671224
Catalog Description	Surface inlet, 6h, 32A, IP67, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2421527
E-Number Norway	1542753
E-Number Sweden	E2417253
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	TBS
Color	Red
Number of Poles	5
Clock Position	6Hour
Rated Current	32 ampere
Rated Voltage	200/346 ... 240/415 volt
Frequency	50 hertz|60 hertz
Degree of Protection	IP67|IP69
Cable Cross-Section	2.5...10 mm²
Housing Material	Thermoplastic (PBT)
Plug Angle	Angled
Product Group	Tough&Safe

DIMENSIONS

Product Net Width	99 millimetre
Product Net Height	138 millimetre
Product Net Length	228 millimetre
Product Net Depth	228 millimetre
Product Net Weight	0.537 kilogram

PACKAGING

Package Width	152 millimetre
Package Height	265 millimetre
Package Gross Weight	0.62 kilogram
Package Length	120 millimetre
Package Units	box 1 piece

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

70218-1116LF 95157-140LF CD15S13E4RV09LF 67996-204HLF 70430-164LF 86093488314745V1LF 86130202123355E1LF 91614-403ALF LD15P33E4GV00LF 68000-236HLF 86093968191755E3LF 86093968813H45V1LF 863013A 68001-200HLF 69192-408HLF DAPO15S365TLF D15P13A6RV12LF LD25S33E4GV00LF RJSBE5080C2 70234-112LF 76384-316LF RJE061661210 54202-G0805CLF 65781-158 DCMF37P 54202-S08-07LF 86093967896755LF DEM09P032N 68001-108HLF 68002116HLF