
Miniature PCB Relay T73

- **10A switching capacity**
- **UL Class F coil insulation system standard**
- **1 form A (NO) and 1 form C (CO) contact arrangement**
- **Flux proof, wash tight plastic sealed case available**



Typical applications
Appliances, HVAC, office machines

Approvals

UL E29244
Technical data of approved types on request

Contact Data

Contact arrangement	1 form A (NO)
Rated voltage	120VAC, 24VDC
Max. switching voltage	120VAC, 28VDC
Rated current	10A
Contact material	AgCdO
Min. recommended contact load	100mA at 5VDC
Frequency of operation	1800 ops./h
Operate/release time max.	10/5ms
Electrical endurance 10A, 120VAC resistive 100x10^3 ops. 6A, 24VDC resistive 100x10^3 ops.	
Contact ratings	10A, 120VAC resistive 6A, 24VDC resistive 3/4HP, 240VAC
Mechanical endurance, DC coil	10x10^6 operations

Coil Data

Coil voltage range	3 to 48VDC
Operative range, IEC 61810	2
Coil insulation system according UL	Class F

Coil Data (continued)

Coil versions, DC coil


Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%	Rated coil power mW
003	3	1.95	0.15	20	450
005	5	3.25	0.25	55.5	450
006	6	3.9	0.3	80	450
009	9	5.85	0.45	180	450
012	12	7.8	0.6	320	450
018	18	11.7	0.9	720	450
024	24	15.6	1.2	1280	450
048	48	31.2	2.4	3491	660

All figures are given for coil without pre-energization, at ambient temperature +23°C.


Insulation Data

Initial dielectric strength	
between open contacts	750V_{rms}
between contact and coil	2000V_{rms}
Clearance/creepage	
between contact and coil	>1.6/3.2mm


Electrical endurance



Operate time



Coil temperature rise



Note: Graphical data should not be used as a substitute for specific application verification.
To be used for estimates only.

04-2011, Rev. 0411
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions


Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Miniature PCB Relay T73 (Continued)


Other Data	
Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customersupport/rohssupportcenter	
Ambient temperature	-30°C to +80°C
Category of environmental protection	
IEC 61810	RTII - flux proof RTIII - wash tight
Shock resistance (functional)	10g
Shock resistance (destructive)	100g
Weight	12g
Resistance to soldering heat THT	
IEC 60068-2-20	RTII: 270°C/10s RTIII: 260°C/5s
Packaging unit	tube/20 pcs., carton box/1000 pcs.

Terminal assignment
Bottom view on solder pins

1 form A (NO)




1 form C (CO)




PCB layout
Bottom view on solder pins


1 form A (NO)



1 form C (CO)



Dimensions



Product code structure — Typical product code: **T73 S 5 D 1 5 -24**

Basic type
T73 Miniature PCB Relay T73

Category of protection
V Flux proof
S Wash tight, immersion cleanable, plastic sealed case

Contact arrangement
1 1 form A (NO) contact **5** 1 form C (CO) contact

Coil input
D DC coil

Relay type
1 Standard coil

Contact material
5 AgCdO

Coil voltage
Coil code: please refer to coil versions table (e.g. 05=5VDC)

Other types on request

Product code	Enclosure	Arrangement	Coil	Cont.material	Coil voltage	Part number
T73S1D15-12	Wash tight	1 form A (NO)	DC coil	AgCdO	12VDC	1-1393197-1
T73S5D15-05		1 form C (CO)			5VDC	2-1393197-9
T73S5D15-12					12VDC	3-1393197-2
T73S5D15-24					24VDC	3-1393197-4

04-2011, Rev. 0411
www.te.com
© 2011 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

1-794222-0 1903112-2 RH73H2A40MKTN 1743455-2 CPF0402B37K4E1 SBCHE154R7K SBCHE64R7K SMW73R0JT 3430B2F51RTDF 3631B101LL 917696-1 1-962915-1 175977-2 2310537-1 936348-1 TE50BR39J 2005330-1 CRGCQ2010J3K3 MPT100C18RF 2834055-1 3-1393225-0 ROX05SJ18R 1393431-1 141991-2 1969656-1 2377783-2 2-292161-3 2380312-2 650075-000 U5254-000005-030PA