
Automotive MOSFET

OptiMOS™ 7 Power-Transistor


RoHS Infineon Automotive Quality AEC Qualified

PG-TDSON-8-53



Features

- OptiMOS™ power MOSFET for automotive applications
- N-channel – Enhancement mode – Logic Level
- Extended qualification beyond AEC-Q101
- Enhanced electrical testing
- Robust design
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- RoHS compliant
- 100% Avalanche tested



Potential applications

General automotive applications.

Product validation

Qualified for automotive applications. Product validation according to AEC-Q101.

Product Summary

V_{DS}	40	V
$R_{DS(on)}$	0.42	mΩ
I_D (chip limited)	532	A

Type	Package	Marking
IAUCN04S7L004	PG-TDSON-8-53	7N04L004

Table of Contents

Description 1
Maximum ratings 3
Thermal characteristics 4
Electrical characteristics 4
Electrical characteristics diagrams 6
Package outline & footprint 10
Revision history 11
Disclaimer 12

Maximum ratings

at Tj=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	V_{GS}=10 V, Chip limitation[1,2)]	532	A
		V_{GS}=10V, DC current	175	
		T_a=100 °C, V_{GS}=10 V, R_{thJA} on 2s2p[2,3)]	61	
Pulsed drain current[2)]	$I_{D,pulse}$	T_C=25 °C, t_p= 100 µs	1800	
Avalanche energy, single pulse[2)]	E_{AS}	I_D=88 A	510	mJ
Avalanche current, single pulse	I_{AS}	–	175	A
Gate source voltage	V_{GS}	–	±16	V
		limited to duty factor of 1%	+20	V
Power dissipation	P_{tot}	T_C=25 °C	219	W
Operating and storage temperature	T_j, T_{stg}	–	-55 ... +175	°C

Thermal characteristics[2)]

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal resistance, junction - case	R_{thJC}	–	–	0.34	0.69	K/W
Thermal resistance, junction - ambient[3)]	R_{thJA}	–	–	26	–	

Electrical characteristics

at Tj=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=1 mA	40	–	–	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=130 µA	1.2	1.5	1.8	
Zero gate voltage drain current	I_{DSS}	V_{DS}=40 V, V_{GS}=0 V, T_j=25 °C	–	–	1	µA
		V_{DS}=40 V, V_{GS}=0 V, T_j=100 °C[2)]	–	–	32	
Gate-source leakage current	I_{GSS}	V_{GS}=16 V, V_{DS}=0 V	–	–	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=4.5 V, I_D=88 A	–	0.51	0.59	mΩ
		V_{GS}=10 V, I_D=88 A	–	0.37	0.42	
Gate resistance[2)]	R_G	–	–	0.8	–	Ω

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics[2]						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=20 V, f=1 MHz	–	9785	12721	pF
Output capacitance	C_{oss}		–	4918	6390	
Reverse transfer capacitance	C_{rss}		–	162	242	
Turn-on delay time	$t_{d(on)}$	V_{DD}=20 V, V_{GS}=10 V, I_D=88 A, R_G=3.5 Ω	–	10	–	ns
Rise time	t_r		–	11	–	
Turn-off delay time	$t_{d(off)}$		–	93	–	
Fall time	t_f		–	46	–	
Gate Charge Characteristics[2]						
Gate to source charge	Q_{gs}	V_{DD}=20 V, I_D=88 A, V_{GS}=0 to 10 V	–	24	32	nC
Gate to drain charge	Q_{gd}		–	25	37	
Gate charge total	Q_g		–	146	190	
Gate plateau voltage	$V_{plateau}$		–	2.5	–	V
Reverse Diode						
Diode continous forward current[2]	I_S	T_C=25 °C	–	–	175	A
Diode pulse current[2]	$I_{S,pulse}$	T_C=25 °C, t_p= 100 µs	–	–	1800	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=88 A, T_j=25 °C	–	0.8	0.95	V
Reverse recovery time[2]	t_{rr}	V_R=20 V, I_F=50A, di_F/dt =100 A/µs	–	58	88	ns
Reverse recovery charge[2]	Q_{rr}		–	69	137	nC

[1] Practically the current is limited by the overall system design including the customer-specific PCB.


[2] The parameter is not subject to production testing – specified by design.

[3] Device on 2s2p FR4 PCB defined in accordance with JEDEC standards (JESD51-5, -7). PCB is vertical in still air.

Electrical characteristics diagrams


1 Power dissipation

$P_{tot} = f(T_C)$; $V_{GS} \geq 6$ V




2 Drain current

$I_D = f(T_C)$; $V_{GS} \geq 6$ V




3 Safe operating area

$I_D = f(V_{DS})$; $T_C = 25$ °C; $D = 0$; parameter: t_p




4 Max. transient thermal impedance

$Z_{thJC} = f(t_p)$; parameter: $D=t_p/T$




5 Typ. output characteristics

$I_D = f(V_{DS})$; $T_j = 25$ °C; parameter: V_{GS}




6 Typ. drain-source on-state resistance

$R_{DS(on)} = f(I_D)$; $T_j = 25$ °C; parameter: V_{GS}




7 Typ. transfer characteristics

$I_D = f(V_{GS})$; $V_{DS} = 6$V: parameter: T_j




8 Typ. drain-source on-state resistance

$R_{DS(on)} = f(T_j)$; parameter: I_D, V_{GS}




9 Typ. gate threshold voltage

$V_{GS(th)} = f(T_j)$; $V_{GS} = V_{DS}$; parameter: I_D




10 Typ. capacitances

$C = f(V_{DS})$; $V_{GS} = 0$ V; $f = 1$ MHz




11 Typical forward diode characteristics

$I_F = f(V_{SD})$; parameter: T_j




12 Typ. avalanche characteristics

$I_{AS} = f(t_{AV})$; parameter: $T_{j(start)}$




13 Typical avalanche energy

$E_{AS} = f(T_j)$; parameter: ID




14 Drain-source breakdown voltage

$V_{BR(DSS)} = f(T_j)$; $I_{D_typ} = 1$ mA




15 Typ. gate charge


$V_{GS} = f(Q_{gate})$; $I_D = 88$ A pulsed; parameter: V_{DD}



16 Gate charge waveforms




Package Outline



1) EXCLUDE MOLD FLASH
2) REMOVAL ON MOLD GATE, INTRUSION 0.1MM AND PROTRUSION 0.1MM
3) LEAD LENGTH UP TO ANTI FLASH LINE
4)ALL METAL SURFACE ARE PLATED, EXCEPT AREA OF CUT
ALL DIMENSIONS ARE IN UNITS MM
THE DRAWING IS IN COMPLIANCE WITH ISO 128 & PROJECTION METHOD 1 [ ]


All dimensions are in units mm

Footprint



All dimensions are in units mm

Packaging



All dimensions are in units mm

Revision History

Revision	Date	Changes
Revision 1.0	15.11.2023	Final Data Sheet

Trademarks
All referenced product or service names and trademarks are the property of their respective owners.

Edition 2023-11-15

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2023 Infineon Technologies AG

All Rights Reserved.

Do you have any questions about any aspect of this document?

Email: erratum@infineon.com

Document reference
IAUCN04S7L004-Data-Sheet-10-Infineon

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications. The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (**www.infineon.com**).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact the nearest Infineon Technologies Office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Infineon Technologies:

TD340N22KOFXPSA1 TLE6250G V33 TLS4120D0EPVXUMA1 TLE5046IC-AK-LR IDH12SG60C
BTS 5210 G IPB042N10N3 G TDA21590 BSS126IXTSA1 IPT60R016CM8XTMA1 IR2302STRPBF
IRF7853TRPBF IRF5210PBF CY8C29466-24SXIT EVALPMG1B1DRPTOBO1 FF800R12KE7EHPSA1
IPD60R280P7S IPD60R360P7S IPF012N06NF2SATMA1 IRF3710PBF IRF7820TRPBF BSC077N12NS3 G
CY15V108QN-20LPXC IPW60R018CFD7XKSA1 IRFP2907PBF IMWH170R450M1XKSA1
IPF010N04NF2SATMA1 IPW60R070CFD7 IR3895MTRPBF IRFS4227TRLPBF