


This document contains proprietary information and such informationmay not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	———	H.wei	19/03/17	19/03/17





Recommended Mounting Hole



1 Electrical

1.1 Impedence	50Ω
1.2 Frequency	DC-6GHz
1.3 VSWR	1.04+0.0045xF(GHz)

2 Environmental&Mechanical

2.1 Temperature range	-55℃～125℃
2.2 RoHs Compliant	
2.3 Durability	>500 cycles

3 Materials&Finish

3.1 Body:	Brass, Suco-plated
3.2 Insulator:	Teflon
3,3 Contact Pin:	Bronze, gold plated

Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 19/03/17	TITLE: RF Coaxial Connector N Female Straight Flange Connector				
ENGINEER: L.yu 19/03/17					
APPROVED: W.yi 19/03/17					
TOLERANCES UNLESS OTHERWISE SPECIFIED X ±0.50 .X ±0.20 .XX ±0.10 ANGLES ±1°		HenryTech			
	PART NO: HL-MCX-KWHD	DIMENSION IN MILLIMETERS (mm)			
		SIZE: A4	SCALE: N/A	SHEET: 1/1	REV: A

HenryTech HenryTech HenryTech HenryTech HenryTech

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HenryTech:

H2SYDC-20-62HP+ HG-SCN-2-22+ HN-DC2016-0.5(12-4.6)M HN-LP7-0.5-1.27(9.4-2.8) HX-N-JK H3-MABA-010551-CF1071 H3-MAPD-008109-C30040 HL-SMA-KHD4 HL-SMA/SMB-KK HL-SSMA-KHD-1 HLCC2250G HT-BFHKI-1572+ HT-LFCG-1700+ H3-MABA-007871-CT1A40 HG-SCN-2-65+ HL-N-KKC HL-SMB-K3DY HT-LFCG-530+ HT-LFCN-3800+ HL-SMAMF-2-18-15dB H3-MABA-011085 HX-SMA/SMP-JK HT-QCN-19+ HT-HFCN-3800+ HT-SCA-4-10+ H3-TC1-1TG2+ HL-MCX-KE-02 HT-HFCN-2700+ HT-LFCN-400+ HX-1.85-JJ