Molded Metal Film Resistors




FEATURES

- 0.25 W to 1 W at 70 °C
- According to NF C 83-230 (RC21U-31U-41U-32)
- According to CECC 40 100
- High insulation > 10^7 MΩ
- Great mechanical strength
- Termination = pure matte tin
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Pb-free

RoHS COMPLIANT

DIMENSIONS in millimeters



SERIES	A max.	Ø B max.	Ø C	WEIGHT in g
RCMM02	6.5 ± 0.2	$2.5\ ^{-0}_{-0.2}$	0.6	0.26
RCMM05	10.2 ± 0.2	3.65 ± 0.1	0.6	0.46
RCMM1	16 ± 0.5	6.2 ± 0.2	0.8	1.30

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	RESISTANCE RANGE Ω	RATED POWER $P_{70\ °C}$ W	LIMITING ELEMENT VOLTAGE V	TOLERANCE ± %	TEMPERATURE COEFFICIENT ± ppm/°C
RCMM02	1 to 332K	0.25	300	2, 5	50, 100
	1 to 332K	0.50	350	2, 5	50, 100
RCMM05	1 to 1M	0.50	350	2, 5	50, 100
RCMM1	1 to 2.26M	1.0	500	2, 5	50, 100

TECHNICAL SPECIFICATIONS

VISHAY SFERNICE SERIES		RCMM02		RCMM05	RCMM1
CECC 83-230 (for information)		RC21U	RC32	RC31U	RC41U
CECC 40 100-802 (for information)		BV	-	CV	-
Power rating at 70 °C		0.25 W	0.50 W	0.50 W	1 W
Resistance value range in relation to tolerance	± 5 %	1 Ω to 330 kΩ E24	1 Ω to 330 kΩ E24	1 Ω to 1 MΩ E24	1 Ω to 2.2 MΩ E24
	± 2 %	1 Ω to 332 kΩ E48	1 Ω to 332 kΩ E48	1 Ω to 1 MΩ E48	1 Ω to 2.26 MΩ E48
Maximum voltage		300 V	350 V	350 V	500 V
Critical resistance		-	245 kΩ	245 kΩ	250 kΩ
Temperature coefficient	Rated in the range -55 °C +155 °C	K2 ≤ ± 100 ppm/°C			
	Typical in the range -10 °C +70 °C	≤ ± 50 ppm/°C			
Insulation resistance (typical)		≥ 10^7 MΩ (500 V_{DC})			
Voltage coefficient		≤ ± 10 ppm/V			
Environmental specifications		-65 °C / +155 °C / 56 days			

For technical questions, contact: sferfixedresistors@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


PERFORMANCE

TESTS	CONDITIONS	REQUIREMENTS	TYPICAL VALUES AND DRIFTS
Load life at max. category temperature	1000 h at 125 °C 35 % of P_n	≤ ± (2 % + 0.1 Ω) Insulation resist. > 1 GΩ	± 0.75 % or 0.05 Ω Insulation resist. 10^6 MΩ
Short time overload	2.5 Un / 5 s Limited to 2 Um	≤ ± (0.5 % + 0.05 Ω)	± 0.2 % or 0.05 Ω
Damp heat humidity (steady state)	56 days with low load	≤ ± (2 % + 0.1 Ω) Insulation resist. > 100 MΩ	± 0.5 % or 0.05 Ω Insulation resist. 10^6 MΩ
Rapid temperature change	-55 °C +125 °C	≤ ± (0.5 % + 0.05 Ω)	± 0.1 % or 0.05 Ω
Climatic sequence	-55 °C +125 °C	≤ ± (2 % + 0.1 Ω) Insulation resist. > 100 MΩ	± 0.1 % or 0.05 Ω Insulation resist. 10^6 MΩ
Terminal strength	Pull - twist - 2 bends	≤ ± (0.5 % + 0.05 Ω)	± 0.05 % or 0.05 Ω
Vibration	10 Hz to 500 Hz	≤ ± (0.5 % + 0.05 Ω)	± 0.05 % or 0.05 Ω
Soldering (thermal shock)	+260 °C, 10 s	≤ ± (0.5 % + 0.05 Ω)	± 0.1 % or 0.05 Ω
Load life	Cycle 90'/30' 1000 h at P_n at 70 °C	≤ ± (2 % + 0.1 Ω) Insulation resist. > 1 GΩ	± 0.5 % or 0.05 Ω Insulation resist. 10^6 MΩ
Shelf life	1 year ambient temperature	-	± 0.1 % or 0.05 Ω


Note

- RC41: 15 s

POWER RATING



TEMPERATURE RISE



MARKING

Printed: Vishay Sfernice trademark, series, ohmic value (in Ω), tolerance (in %), temperature coefficient, manufacturing date. Due to lack of space RCMM02 is printed MM02.

GLOBAL PART NUMBER INFORMATION

R	C	M	M	0	2		1	3	0	1	J	K	S	1	4

GLOBAL MODEL	SIZE	SPECIAL	OHMIC VALUE	TOLERANCE	TEMPERATURE COEFFICIENT	PACKAGING
RCMM	**02** **05** **10**	As applicable. Contact us.	The first three digits are significant figures and the last digit specifies the number of zeros to follow. R designates decimal point. **1301** = 1.3 kΩ **3301** = 3.3 kΩ **22R0** = 22.0 Ω **1R22** = 1.22 Ω	**G** = 2 % **J** = 5 %	**K** = K2, 100 ppm/K	AM500 = **A20** AM1000 = **A22** BAG100 = **S14** BAG50 = **S09**

For technical questions, contact: sferfixedresistors@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

© 2021 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Vishay Intertechnology:

SMC3K43CAHM3_A/H T6N43AHM3/H VOH260A-X017T CRCW08052K15FKEA CRCW08053K92FKEA M55342K11B34E0PS2 V40PWL63CHM3/I VOA300-EF-X017T VOT8121AM-T ZPY5V6-TAP P6SMB43CAHM3_A/H V10PWM153HM3/I RNC50H3482FSB14 SMC3K90CAHM3_A/H VO2611-X007T NTCS0603E3102JLT SIC951ED-Y1-GE3 SMA6F90A-M3/H TSM4YJ502KB25 VS-GT50LA65UF ACASA470124701P100 MMA02040E9102BB100 SMC3K10CAHM3_A/H SQ7415CENW-T1_GE3 SQJ140ELP-T1_GE3 T15B43AHM3/H T55P106M010C0200 TNPW04026K49BEED NTCLE100E3152JB0 AS1FJ-M3/H