DATA SHEET

COAXIAL CONNECTOR, TNC, 50 Ohm, Straight bulkhead cable jack (female)

24_TNC-50-2-1/133_N

Properties

- Threaded coupling mechanism improves control over the interface dimensions
- Used under a higher environmental load than BNC
- Available for 50 ohm and 75 ohm applications
- Applicable in frequencies up to 11 GHz

Interface and material data		
Piece parts	Material	Plating

Ordering Information Table	
Item number	Item description
22543398	24_TNC-50-2-1/133_NE

Suitable cables	
Cable group	X3 - 2 mm / 50 Ohm

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P31321 / Date of publication: 25.11.2023 / uncontrolled copy

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

Minibend L-10 85201112 G032D/BNCm/BNCm/1000 G032D/Nm/SMAm/1000 G_03130_HT-01
16_MMCX-50-2-4/111_OH MINIBEND R-10 11_SMC-50-2-10/111_NE 11_TNC-50-3-116/133_NE
1399.31.0020 6601_PC185-50-1/199_NE 84093961 RG_196_A/U 6806.19.A 11MMBXEF31616MMBX/300
12012090 1399.17.0210 1399.17.0231 23000457 MINIBEND R-12 PCRS_LCMX_LCMX_O421T_30.0_LL
12535682 23002145 33_PC24-SK-50-2/199_NE 84118385 RADOX 125 0.75 MMÂ² RED 22511964
6620_SMA-50-2/199_NE 24_SMA-50-2-15/111_NH MINIBEND R-8