TECH PUBLIC
台舟电子

AZC002-02N

Low Capacitance TVS Diode Array

www.sot23.com.tw

Features

- Ultra low leakage: nA level
- Operating voltage: 5V
- Low clamping voltage
- Complies with following standards:
  – IEC 61000-4-2 (ESD) immunity test
    Air discharge: ±30kV
    Contact discharge: ±30kV
  –IEC61000-4-5 (Lightning) 6A (8/20μs)
  – IEC61000-4-4 (EFT) 40A (5/50ns)
- RoHS Compliant


Mechanical Characteristics


- Package: SOT-143
- Lead Finish: Matte Tin
- Case Material: “Green” Molding Compound.
- UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 3 per J-STD-020
- Shipping Qty :3000pcs/7Inch Tape & Reel

Applications

- USB 2.0 power and data line
- Set-top box and digital TV
- Digital video interface (DVI)
- Notebook Computers
- SIM Ports
- 10/100 Ethernet

Dimensions and Pin Configuration





Marking: C04TP

Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppk	100	W
Peak Pulse Current (8/20μs)	Ipp	6	A
ESD per IEC 61000−4−2 (Air) ESD per IEC 61000−4−2 (Contact)	V_{ESD}	±30 ±30	kV
Operating Temperature Range	T_J	−55 to +125	°C
Storage Temperature Range	Tstg	−55 to +150	°C

Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			5	V	
Breakdown Voltage	V_{BR}	6.5			V	I_T = 1mA
Reverse Leakage Current	I_R			0.08	uA	V_{RWM} =5V
Clamping Voltage	V_C			10	V	I_{PP} = 1A (8 x 20μs pulse)
Clamping Voltage	V_C			15	V	I_{PP} = 6A (8 x 20us pulse)
Junction Capacitance	C_J		0.8	0.9	pF	VR = 0V, f = 1MHz (IO to GND)
Junction Capacitance	C_J		0.3		pF	VR = 0V, f = 1MHz (IO to IO)

Typical Performance Characteristics (T_A=25°C unless otherwise Specified)

Fig1. 8/20μs Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)







Fig3. Power Derating Curve




Outline Drawing - SOT-143





DIM	DIMENSIONS					
	INCHES			MILLIMETERS		
	MIN	NOM	MAX	MIN	NOM	MAX
A	.031	-	.048	0.80	-	1.22
A1	.000	-	.006	0.013	-	0.15
A2	.029	.035	.042	0.75	0.90	1.07
b	.011	-	.020	0.30	-	0.51
b1	.029	-	.037	0.76	-	0.94
c	.003	-	.008	0.08	-	0.20
D	.110	.114	.120	2.80	2.90	3.04
E	.082	.093	.104	2.10	2.37	2.64
E1	.047	.051	.055	1.20	1.30	1.40
e	.075			1.92 BSC		
e1	.008			0.20 BSC		
L	.015	.020	.024	0.40	0.50	0.60
L1	(.021)			(0.54)		
N	4			4		
θ	0°	-	8°	0°	-	8°
aaa	.006			0.15		
bbb	.008			0.20		
ccc	.004			0.10		

Land Pattern -SOT-143



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
C	2.20	0.087
E1	1.92	0.076
E2	1.72	0.068
G	0.80	0.031
X1	1.00	0.039
X2	1.20	0.047
Y	1.40	0.055
Z	3.60	0.141

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TECH PUBLIC:

LTH7 TPDMG6602SVT TPESD0504S6-A TPFMMT493 DMP6350S FDMS7670AS-TP IRFR2405TRPBF-TP TPAPX809S-31SA TPB1A30-123 BSN20W TPADM809SAKSZ TPS3809L30DBVR-TP DDTA143ZCA QM3003J-TP TPB05A40-323 TPD1213A-02SM TPS7B6950DBVR-TP TPSPX3819M5-L-3-3 TPWSB5557Z TPADM809LAKSZ BV15C FDC6301N-TP TPZVN3320FTA ESD5B5.0ST1G-P SN7002W TPESD0402G08V SI3932DV TPESD5311N TPGC12C-1 TPZXMP3A13FTA