
REV.	DATE	DESCRIPTION
A	06/29/04	UPDATE DRAWING FORMAT
B	03/27/05	ADD 17.5 HEX DIMNSION



CRIMP NOTES:

1. CRIMPED FERRULE
   HEX CRIMP SIZE .128"
2. CRIMPED CONTACT PIN
   SQ. CRIMP SIZE .7mm
3. MAX. PANEL THICKNESS= 5.5mm

8				
7	FERRULE	COPPER	NICKEL	1
6	HEX NUT	BRASS	NICKEL	1
5	LOCK WASHER	BRASS	NICKEL	1
4	GASKET	RUBBER	RED	1
3	CONTACT PIN	BRASS	GOLD	1
2	INSULATOR	DELRIN	NATURAL	1
1	BODY	BRASS	NICKEL	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [ ] ARE IN INCHES AND FOR CUSTOMER REFERANCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:

0.5 – 8mm ± 0.20mm
8 – 30mm ± 0.40mm
30 – 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:

.020 – .315 = ± 0.007"
.315 – 1.180 = ± 0.015"
1.180 – 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN G.R.S.	03/27/05
CHECKED	
ISSUED	
SHEET 1 OF 1	

CAD FILE C:/122/122370.DWG

Amphenol Connex

PART DESCRIPTION
TNC BULKHEAD CRIMP JACK
(FOR RG–178B/U, 196A/U CABLE)

PART NO. 122370

DWG. NO.	REV.	SIZE	SCALE
122370.DWG	B	A	NA

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

LD25S33E4GV00LF 86093488314745V1LF 67996-204HLF 68001-108HLF 91614-403ALF 95157-140LF LD15P33E4GV00LF RJE061661210 54202-G0805CLF DAPO15S365TLF DEM09P032N 54202-S08-07LF 68000-236HLF 70234-112LF 70430-164LF 68002116HLF 86093968813H45V1LF 863013A RJSBE5080C2 65781-158 68001-200HLF 86093967896755LF 86093968191755E3LF D15P13A6RV12LF 69192-408HLF 70218-1116LF CD15S13E4RV09LF 76384-316LF 86130202123355E1LF DCMF37P