
Air solenoid valve
CPE14-M1BH-5L-QS-8

Part number: 196912





General operating condition

Data sheet

Feature	Value
Valve function	5/2, monostable
Actuation type	Electrical
Width	14 mm
Standard nominal flow rate	680 l/min
Pneumatic working port	QS-8
Operating voltage	24V DC
Operating pressure	0.3 MPa ... 0.8 MPa
Operating pressure	3 bar ... 8 bar
Structural design	Piston gate valve
Reset method	Pneumatic spring
Certification	c UL us - Recognized (OL)
Maritime classification	See certificate
Certificate issuing authority	DNV-TAA000032X UL MH19482
Degree of protection	IP65 With plug socket as per IEC 60529
Nominal width	6 mm
Exhaust air function	With flow control option
Sealing principle	Soft
Mounting position	Any
Manual override	Detenting via accessory Non-detenting
Type of control	Pilot-controlled
Pilot air supply port	Internal
Flow direction	Non-reversible
Symbol	00991023
Valve position ID	Label holder
Lap	Overlap
Switching time off	32 ms
On switching time	24 ms
Duty cycle	100% in combination with holding current reduction
Max. positive test pulse with 0 signal	1200 µs
Max. negative test pulse on 1 signal	900 µs
Coil characteristics	24 V DC: 1.28 W
Permissible voltage fluctuations	-15 % / +10 %
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]

Feature	Value
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Vibration resistance	Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Temperature of medium	-5 °C ... 50 °C
Ambient temperature	-5 °C ... 50 °C
Electrical connection	2-pin
Type of mounting	With through-hole
Pilot exhaust air port 82	M3
Pilot exhaust air port 84	M3
Pilot air port 12	M3
Pilot air port 14	M3
Pneumatic connection 1	QS-8
Pneumatic connection 2	QS-8
Pneumatic connection 3	G1/8
Pneumatic connection 4	QS-8
Pneumatic connection 5	G1/8
Note on materials	RoHS-compliant
Seals material	NBR
Housing material	Die-cast aluminum

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQH-T-G38-Q8-P10 VABM-L1-14W-G14-4-GR NPQP-D-R14-Q10-FD-P10 DSBC-40-160-D3-PPSA-N3 DSBC-50-20-D3-PPSA-N3 QS-G1/8-6-I NPQP-D-R38-Q10-FD-P10 DSBC-32-50-D3-PPVA-N3 QS-G3/8-12 VABM-L1-18S-G38-10 VABM-L1-10HW-G18-4-GR HGL-1/8-B SPTW-P16R-G14-A-M12 QSLV-G1/4-6 QSL-1/4-4 DSBC-32-40-D3-PPVA-N3 VABM-B10-25S-G38-4-P3 NPQH-D-S14-Q8-P10 NPQH-D-Q14-E-P10 SEA-3GS-M8-S VABM-B10-25S-G38-6 DSBC-63-320-D3-PPVA-N3 VABM-B10-20S-G14-6 DSBC-40-50-D3-PPSA-N3 DFM-63-100-P-A-KF QSLV-G1/8-8 QSL-12 NPQH-D-Q12-Q8-P10 QSLV-G1/2-12-I 153034