INDUSTRIAL@AMPHENOL TRUSTED GLOBALLY

432RAU6W

Panel mounted socket

2CMA166982R1000



Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 32A, IP67 watertight, unified flange, angled, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

GENERAL

Product Name	Panel mounted socket
Product ID	2CMA166982R1000
Function	Socket outlet, panel mounting, unified flange, angled
EAN	7392696669825
Catalog Description	Socket-outlet, panel mounting, 6h, 32A, IP67, unified flange, angled, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2421277
E-Number Norway	1561953
E-Number Sweden	E2416735
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	TRAU
Color	Red
Number of Poles	5
Clock Position	6Hour
Rated Current	32 ampere
Rated Voltage	200/346 … 240/415 volt
Frequency	50 hertz|60 hertz
Degree of Protection	IP67|IP69
Cable Cross-Section	2.5…10 mm²
Housing Material	Thermoplastic (PBT)
Plug Angle	Angled
Product Group	Tough&Safe

DIMENSIONS

Product Net Width	99 millimetre
Product Net Height	118 millimetre
Product Net Length	118 millimetre
Product Net Depth	118 millimetre
Product Net Weight	0.32 kilogram

PACKAGING

Package Width	112 millimetre
Package Height	139 millimetre
Package Gross Weight	0.37 kilogram
Package Length	112 millimetre
Package Units	box 1 piece

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Amphenol:

70430-164LF 86093967896755LF 91614-403ALF DEM09P032N LD15P33E4GV00LF 65781-158 67996-204HLF 68000-236HLF 69192-408HLF DCMF37P 68002116HLF 86093968191755E3LF 86093968813H45V1LF 86130202123355E1LF 95157-140LF 76384-316LF 54202-S08-07LF 70234-112LF CD15S13E4RV09LF D15P13A6RV12LF RJE061661210 70218-1116LF 863013A DAPO15S365TLF 86093488314745V1LF RJSBE5080C2 68001-108HLF 68001-200HLF LD25S33E4GV00LF 54202-G0805CLF