




ROHS











Recommended PCB Layout

SPECIFICATIONS

1.RATING: DC30V 1.0A
2.MECHANICAL LIFE: 10,000 CYCLES.
3.PACKAGING: 1000PCS/REEL

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
③	Shell	——	1	Phosphor Bronze	Sn Plated	——
②	Contact	——	5	C2680R-H	Au Plated	——
①	Housing	——	1	LCP	Black	——

APPROVALS		DATE
DRAWN	JKUN.LU	2014.5.29
CHECKED		
APPROVALS		

HRO 鹤荣® ELECTRONICS CO.,LTD

TITLE:	USB CONNECTOR
PART NO.	U-C-M5DD-Y-3
UNIT: mm	SCALE: 1:1
DRAWING NO.	——
PROJ:	SHEET 1 OF 1

TOLERANCES ARE			ANGLE
	30~以下	±0.30	
	10~30	±0.25	
	5~10	±0.20	±2°
	~ 5	±0.15	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
——	B	——	1	——	——	——
——	A	——	NEW	——	——	——

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HRO:

DS-01BP K2-1102DP-G4SW-04 PJ-3250-5A U-F-M5DD-Y-L1 K3-1346S-F1 K5-1617SA-01 SS-22D03-G4 U-F-M5DS-Y-1 U-M-M5DD-W-2 U-C-M5DW-W-1 U-F-M5DD-Y-L DC-031A-10A K2-1102DP-S3SW-04 K2-1102SP-K4SC-04 K2-1102AT-A4CW-01 K2-1102SP-A5SC-04 U-C-M5SS-Y-1 DA-10RP DQ-03BP K3-2258S-E1 SIM-08A TYPE-C-31-M-04 U-F-M5DD-W-L PJ-399B-6A U-F-M5SS-W-5 K2-1818DP-A3SW-01 ES-07KP K2-1101DF-A4DW-01 K2-1102BG-I4CW-01 K8-5851D-L1