
Product data sheet
Subminiature connectors

Product description	**Bayonet Female cable connector, Contacts: 4, 3.0-4.0 mm, unshielded, solder, IP40**
Area	**series 710**
Part no.	**99 0980 100 04**


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 0980 100 04
Connector design	Female cable connector
Version	Connector socket straight
Connector locking system	Bayonet
Termination	solder
Degree of protection	IP40
Cross-sectional area	max. 0.25 mm² / AWG 24
Cable outlet	3.0-4.0 mm
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	2.58
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	125 V
Rated impulse voltage	1500 V
Rated current	3,0 A
Insulation resistance	≥ 10^{10} Ω
Pollution degree	1
Overvoltage category	II
Insulating material group	III
EMC compliance	unshielded

Product data sheet
Subminiature connectors

Product description	**Bayonet Female cable connector, Contacts: 4, 3.0-4.0 mm, unshielded, solder, IP40**
Area	**series 710**
Part no.	**99 0980 100 04**

Material

Housing material	PA
Contact body material	PA (UL94 V-0)
Contact material	CuSn (bronze)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	e5b461cf-4fd9-4828-9d1f-a60b54e8cf5d

Classifications


eCl@ss 11.1	27-44-01-02
ETIM 9.0	EC002635

Declarations of conformity

Low Voltage Directive	2014/35/EU (EN 60204-1:2018;EN 60529:1991)

Assembly instructions

1. *Bead pressing screw to cable.*
2. *Dismantle cable to 15 mm length.*
3. *Strip and solder single wires.*
4. *Place female insert into carrier sleeve part 2 (lower part grey).*
4. *Mount carrier sleeve part 1 (upper part black) on carrier sleeve part 2 (lower part grey).*
5. *Snap assembly group into coupling ring.*
6. *Tighten pressing screw.*



Date: 20.07.2024

Product data sheet
Subminiature connectors

Product description	**Bayonet Female cable connector, Contacts: 4, 3.0-4.0 mm, unshielded, solder, IP40**
Area	**series 710**
Part no.	**99 0980 100 04**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

The plug connector is not suitable for mains voltages Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Franz Binder:

09 0137 70 04 79 5001 20 04 99-3400-00-03 04 0722 000 09-3491-90-12 09-3105-86-03 09-9749-20-03 14402780 99-0401-10-02 99-3376-100-04 99-9115-00-05 09-3481-679-08 79-3468-52-06 99-0072-100-02 99-0491-12-12 99-0609-00-04 09-0981-00-04 99-4929-00-08 09 3463 00 06 09-3432-500-04 09-3442-92-05 99-0430-27-04 99-4905-00-03 99-9475-100-07 09-0315-00-05 09-0498-00-24 99-0096-100-05 86 6919 0002 00703 99 0975 102 03 99-0429-314-04