Heatsinks f.cool
Cases f.case
Connectors f.con
- Sockets
- PCB connectors
  - Male headers
  - Female headers
  - Direct female connectors
  - Jumpers
- IDC-connectors
- D-Sub connectors
- Brackets for PC
- Optoelectronics

Female headers

BL 1 ...

BL 1 26 Z

Stamped contact spring (fork contact), for □ 0.635 mm
separable! any requested number of contact can be delivered

Data sheet | add to request



Features | Technical Drawing | Service | Accessories / related products

grid	2.54 mm
no. of contacts	26
contact material	CuSn alloy
surface of contact	tin-plated
surface contact /	Ni+≥0.2µm Au
contact sleeve	Ni+4...6µm Sn
type internal spring	fork contact
plugability for circuit points	□0,5...0,7mm
insert depth	1.5...5mm
plug-in cross-section	□0,635mm
insertion / drawing force	1.5 N/1.3 N
volume resistance	≤10 mΩ
capacity between two adjacent contacts	≤ 0,9 pF
nominal current	3 A
nominal voltage	125 V AC
test voltage	1500 V
insulating body material	PPS
temperature range	-40°C... +200°C (260°C/10 s)
class of inflammability	UL 94 V-0
version	stamped contact spring (fork contact)
specific insulation resistance	$>10^{12}$ Ω·m
connection type	-
reflow solderable	yes

Fischer Elektronik GmbH & Co. KG
Nottebohmstraße 28, 58511 Lüdenscheid, DEUTSCHLAND
: +49 2351 435-0, info@fischerelektronik.de

Downloaded from Arrow.com.