
CUI DEVICES



## MODEL: PJ-012A | DESCRIPTION: DC POWER JACK

### FEATURES
- 2.0 mm center pin
- 5.0 A rating
- right-angle orientation
- through hole



RoHS

## SPECIFICATIONS

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| rated input voltage | | | 24 | | Vdc |
| rated input current | | | | 5.0 | A |
| contact resistance[1] | | | | 30 | mΩ |
| insulation resistance | at 500 Vdc | 100 | | | MΩ |
| voltage withstand | for 1 minute | | | 500 | Vac |
| insertion/withdrawal force | | 0.3 | | 3 | kg |
| operating temperature | | -25 | | 70 | °C |
| life | | | 5,000 | | cycles |
| flammability rating | UL94V-0 | | | | |
| RoHS | yes | | | | |


Note: 1. When measured at a current of less than 100 mA/1 kHz

## SOLDERABILITY


| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| hand soldering | for 3~5 seconds | | | 360 | °C |


## MECHANICAL DRAWING


units: mm[inches]
tolerance: ±0.3 mm
unless otherwise noted




| | MATERIAL | PLATING |
|---|---|---|
| center pin | copper | nickel |
| terminal 1 | brass | silver |
| terminal 2 | titanium copper alloy | silver |
| terminal 3 | brass | silver |
| plastic | PBT | |









PCB LAYOUT
TOP VIEW




MATING PLUG
Jack Insertion Depth: 6.7 mm

| SCHEMATIC |  |
|---|---|
| Model | PJ-012A |
| Center Pin | Ø2.0 mm |



Note: 1. All specifications measured at 10~35°C, humidity at 45~85%, under standard atmospheric pressure, unless otherwise noted.

## REVISION HISTORY

| rev. | description | date |
|---|---|---|
| 1.0 | initial release | 05/17/2006 |
| 1.01 | brand update | 06/02/2020 |

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**cuidevices**.com

# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## Same Sky:

PJ-066B PTN10-A500HB20 UJ31-CH-G-SMT-TR-67 HSS-B20-061H IA-MM6335B PR12-5V-360-1A SJ-43514-SMT-TR SP-35401 TBL008V-1000-07BE CMI-1275C-050 CFM-8020V-133-380 SR10-3V-450-2C SJ-3504 AMT-17C-1-036 AMT103-V CFM-5015V-150-290 UJ2-AV-1-TH PD-40 SJ2-35954D-SMT-TR IA-MS6335B CEP-1130 CMM-3729AB-38308-TR PS04-G16MP-A4W SR10-5V-450-2C TB005-762-03BE SJ2-2533B-SMT-TR TBL002A-350-16GY-2GY CPT-2745-L100 CDM1232-03A-02MST-1M-67 CMI-9653S-SMT-TR