Barb fitting
CN-M3-PK-3

Part number: 15872



General operating condition

Data sheet

Feature	Value
Nominal width	1.5 mm
Type of seal on screwed plug	Sealing ring
Operating pressure for entire temperature range	-0.95 bar ... 10 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Ambient temperature	0 °C ... 60 °C
Pneumatic connection 1	External thread M3
Pneumatic connection 2	for pneumatic tubing outside diameter 4 mm
Note on materials	RoHS-compliant
Housing material	High-alloy steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DSBC-50-20-D3-PPSA-N3 NPQP-LQ-R18-Q4-FD-P10 QSLL-1/4-4 SPTE-V1R-Q3-V-2.5K
DSBC-32-40-D3-PPVA-N3 DSBC-80-320-D3-PPVA-N3 MSFW-110-50/60-DS N-1/8-P-6
NPQH-T-G38-Q8-P10 NPQP-D-Q4-S8-FD-P10 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q8-FD-P10
NPQP-Y-Q6-E-FD-P10 QH-1 1/2 DSBC-63-320-D3-PPVA-N3 DSNU-12-60-P-A QSS-8-F
DSBC-32-50-D3-PPVA-N3 QS-1/2-16 QSML-6 VBQF-U-G14-E CRVZS-0.4 DFM-63-100-P-A-KF
NPQP-Y-R12-Q12-FD QSML-3 VABM-L1-18W-G38-8-G DSBC-80-250-D3-PPSA-N3 SNC-63
PUN-H-4X0,75-TBL QSLV-G1/4-6