CUI DEVICES

MODEL: PJ-004CH | DESCRIPTION: DC POWER JACK

FEATURES

- 1 mm center pin
- 3.5 A rating
- shielded
- panel mount



RoHS

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			24		Vdc
rated input current				3.5	A
contact resistance[1]	between terminal and mating plug between terminal in a closed circuit			50 30	mΩ mΩ
insulation resistance	at 500 Vdc between adjacent contacts	100			MΩ
voltage withstand	for 1 minute, 0.5 mA between adjacent contacts			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life	at a rate of 24 cycles/minute		5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				


Note: 1. When measured at a current of less than 100 mA/1 kHz
2. All specifications measured at 10~35°C, humidity at 45~85%, under standard atmospheric pressure, unless otherwise noted.

SOLDERABILITY


parameter	conditions/description	min	typ	max	units
hand soldering	for 3~4 seconds	340	350	360	°C


MECHANICAL DRAWING


units: mm
tolerance:
X.X ±0.2 mm
X.XX ±0.10 mm
X.XXX ±0.050 mm





	MATERIAL	PLATING
center pin	brass	nickel
terminal 1	brass	silver
terminal 2	copper alloy	silver
terminal 3	copper alloy	silver
insulator	PA10T	












MATING PLUG
Jack Insertion Depth: 6.05 mm

SCHEMATIC	
Model	PJ-004CH
Center Pin	Ø1 mm

REVISION HISTORY

rev.	description	date
1.0	initial release	12/13/2018
1.01	brand update	10/22/2019

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

cuidevices.com

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Same Sky:

PD-40 PJ-066B CFM-8020V-133-380 IA-MS6335B CMI-1275C-050 IA-MM6335B TB005-762-03BE TBL002A-350-16GY-2GY TBL008V-1000-07BE AMT-17C-1-036 CMM-3729AB-38308-TR CPT-2745-L100 PTN10-A500HB20 AMT103-V CDM1232-03A-02MST-1M-67 HSS-B20-061H SJ2-35954D-SMT-TR SP-35401 UJ2-AV-1-TH PS04-G16MP-A4W SJ-3504 SR10-3V-450-2C UJ31-CH-G-SMT-TR-67 CFM-5015V-150-290 SR10-5V-450-2C CEP-1130 PR12-5V-360-1A SJ-43514-SMT-TR SJ2-2533B-SMT-TR CMI-9653S-SMT-TR