Surge arrester

2-electrode arrester

Series/Type: **EC350X**
Ordering code: **B88069X0810S102**
Version/Date: Issue 06 / 2015-01-13

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

Surge arrester — B88069X0810S102

2-electrode arrester — EC350X

Features

- Standard size
- Very fast response time
- High current rating
- Stable performance over life
- Very low capacitance
- High insulation resistance
- RoHS-compatible

Applications

- Branch exchange
- Line protection
- Subscriber protection
- Alarm system
- Tuner
- Antenna protection


Electrical specifications

DC spark-over voltage [1) 2)]		350	V
Tolerance		±15	%
Min.		298	V
Max.		402	V
Impulse spark-over voltage			
at 100 V/µs	- for 99% of measured values	< 800	V
	- typical values of distribution	< 700	V
at 1 kV/µs	- for 99% of measured values	< 900	V
	- typical values of distribution	< 800	V
Service life			
10 operations	50 Hz, 1 s	5	A
1 operation	50 Hz, 0.18 s (9 cycles)	20	A
10 operations	8/20 µs	5	kA
1 operation	8/20 µs	10	kA
1 operation	10/350 µs	1	kA
Insulation resistance at 100 V_{DC}		> 10	GΩ
Capacitance at 1 MHz		< 1.5	pF
Arc voltage at 1 A		~ 12	V
Glow to arc transition current		< 0.1	A
Glow voltage		~ 60	V
Weight		~ 1.5	g
Operation and storage temperature		–40 ... +90	°C
Climatic category (IEC 60068-1)		40/ 90/ 21	
Marking, red positive		**EPCOS EC 350 YY O** EC - Series 350 - Nominal voltage YY - Year of production O - Non radioactive	
Certification		UL 497B (E163070)	

1) At delivery AQL 0.65 level II, DIN ISO 2859
2) In ionized mode


Terms in accordance with ITU-T Rec. K.12; IEC 61663-2 and IEC 61643-311.

Dimensional drawing in mm




Ordering code and packing advice

*B88069X0810**S102** = 100 pcs. on 5 taped stripes*



Soldering parameter

Wave soldering



Wave profile features	Pb-free assembly
Solder	Sn 95.5 / Ag 3.8 / Cu 0.7
Solder bath temperature	263 (±3) °C
Dwell time	< 3 s

Soldering profile applied to a single soldering process.

Cautions and warnings

- Do not operate surge arresters in power supply networks, whose maximum operating voltage exceeds the minimum spark-over voltage of the surge arresters.
- Surge arresters may become hot in the event of longer periods of current stress (burn risk). In the event of overload the connectors may fail or the component may be destroyed.
- If the contacts of the surge arresters are defective, current load can cause sparks and loud noises.
- Surge arresters must be handled with care and must not be dropped.
- Do not continue to use damaged surge arresters.

Display of ordering codes for EPCOS products

The ordering code for one and the same EPCOS product can be represented differently in data sheets, data books, other publications, on the EPCOS website, or in order-related documents such as shipping notes, order confirmations and product labels. **The varying representations of the ordering codes are due to different processes employed and do not affect the specifications of the respective products**. Detailed information can be found on the Internet under www.epcos.com/orderingcodes

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application.** As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified.** In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, Alu-X, CeraDiode, CeraLink, CeraPad, CeraPlas, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, LeaXield, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, PQSine, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, TFAP, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TDK:

MMZ1005S601ETD25 B32024A3105M000 B82559A3292A025 FG26X7R2J103KNT00 FHV-153AN
MLF1608D68NMTA00 MLG1005S2N4BTD25 SPM3012T-R47M-LR FHV-5AN MLG1005S7N5JTD25
B82496C3220G000 B82559A7682A024 B88069X5600S102 C3216X7R2A224K115AE MMZ1608S102ATA00
B59886C0120A070 B82477D4333M900 CGA2B1C0G2A681J050BC MLG1005S68NJTD25
B65884E0012D001 B82422A1562J100 CGA2B3X7R1H473K050BD CGA4J2X8R1H104M125AA
B32654A6335K000 B32683A1223J000 B84111A0000A030 CGA2B1X7R1C683M050BC
C3225C0G2A683J230AA FA24C0G1H333JNU00 MLG1005S0N8BTD25