
Pomona ELECTRONICS

Technical Data Sheet

Model 72973
SMA JACK (F) TO JACK (F), PANEL



Model 72973 SMA JACK (F) TO JACK (F), PANEL



High bandwidth, small size, and durability for confident connections

Features

- DC - 18 GHz
- Meets MIL-C-39012, IEC 169-15, CECC 22110.
- Small size and durability for mobile communications.
- Precision machined and gold-plated for low loss.

Materials

- Body is machined brass with gold plating.
- Center Contacts - Plug is gold plated brass and Jack is gold plated Beryllium copper.
- Insulators are high quality PTFE.
- Crimp Ferrules are copper with gold or nickel plating.
- Gaskets are silicone rubber.

Ordering Information

Model: 72973
Description: SMA JACK (F) TO JACK (F), PANEL

Specifications

Impedance	50 Ω
Frequency Range	DC –18 GHz max.
Working Voltage	< 500 Vpeak
Dielectric Withstanding Voltage	1,000 Vrms
VSWR	1.25 max.
Center/Outer Contact Resistance	0.003/0.002 Ω max
Insulation resistance	> 5000 MΩ
Number of Insertions	500 cycles minimum
Temperature Range	-65˚ C to 165˚ C, -85˚ F to 329˚ F

USA: Sales: 800-490-2361
Technical Support: technicalsupport@pomonatest.com
Fax: 425-446-5844
Europe: 31-(0) 40 2675 150 **International**: 425-446-5500
Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.
D2003412 REV 001

Copyright © 2007 11/13/2007

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Pomona Electronics:

B-24-02 6411 72913-2 1825-7 4276-C-24 5697-72 5908A MDP-1 1166-24-2 73087-6-4 1383-C-24 1508/POM 1581-6 1614A-0 4826-2 5253 73087-24-2 MDP-0 B-36-3 2249-C-240 5178 5673B 5901B/POM 5952A 73092-0 73092-9 2249-E-12 72931 73053 AL-B-36-0