

Pomona ELECTRONICS

Technical Data Sheet

Model 72966
SMA JACK (F) / JACK (F)





Model 72966 SMA JACK (F) / JACK (F))

High bandwidth, small size, and durability for confident connections

Features

- DC - 18 GHz
- Meets MIL-C-39012, IEC 169-15, CECC 22110.
- Small size and durability for mobile communications.
- Precision machined and gold-plated for low loss.

Materials

- Body is machined brass with gold plating.
- Center Contacts - Plug is gold plated brass and Jack is gold plated Beryllium copper.
- Insulators are high quality PTFE.
- Crimp Ferrules are copper with gold or nickel plating.
- Gaskets are silicone rubber.

Specifications

Impedance	50 Ω
Frequency Range	DC – 18 GHz max.
Working Voltage	< 500 Vpeak
Dielectric Withstanding Voltage	1,000 Vrms
VSWR	1.25 max.
Center/Outer Contact Resistance	0.003/0.002 Ω max
Insulation resistance	> 5000 MΩ
Number of Insertions	500 cycles minimum
Temperature Range	-65˚ C to 165˚ C, -85˚ F to 329˚ F

Ordering Information

Model: 72966
Description: SMA JACK (F) / JACK (F)

USA: Sales: 800-490-2361
Technical Support: technicalsupport@pomonatest.com
Fax: 425-446-5844
Europe: 31-(0) 40 2675 150 **International**: 425-446-5500
Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.
D2003405 REV 001

Copyright © 2007 10/17/2007

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Pomona Electronics:

2249-C-240 5908A 73092-0 AL-B-36-0 1383-C-24 73053 1166-24-2 4826-2 B-36-3 1508/POM 1825-7 5178 5673B 5901B/POM 73087-24-2 1581-6 5952A 73087-6-4 MDP-0 2249-E-12 5253 6411 MDP-1 4276-C-24 72931 73092-9 B-24-02 5697-72 1614A-0 72913-2