
JMSWD-5XL Product Details



JMSWD-5XL
(1617132-6)
TE Internal Number: 1617132-6
Active

Military/Aerospace High Performance Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- MSD TO-5 Relay Series
- Input Voltage = 5 VDC
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Contact - Rated Current = 1 A
- Non Polarized, Monostable Coil - Magnetic System

View all Features

Add to My Part List | Request Sample | Find Similar Products | Buy Product

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- None Available

Catalog Pages/Data Sheets:
- RELAY (PDF, English)

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files:
- None Available

List all Documents

Additional Information:
- Product Line Information

Related Products:
- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- MOSFET Driver = Without

Mechanical Attachment:
- Mounting Options = PC Board

Electrical Characteristics:
- Input Voltage (VDC) = 5
- Contact - Rated Current (A) = 1
- Coil Suppression Diode = With
- Coil Polarity Protection Diode = Without
- Coil - Resistance (Ω) = 100
- Coil Power Measurement = Milliwatts
- Coil - Rated Power, DC (mW) = 250
- Actuating System = DC
- Shock = 75 G's, 6ms
- Vibration = 30G's, 10 to 3000Hz

Termination Features:
- Termination Type = Long Leads

Body Features:
- Enclosure Type = Hermetically Sealed

Configuration Features:
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Coil - Magnetic System = Non Polarized, Monostable
- Transistor Driver = Without

Industry Standards:
- Government/Industry Qualification = Yes
- Government/Industry Part Number = M39016/16-017L
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Not suitable for lead free processing
- Approved Standards = M39016 Qualified, L Level

Conditions for Usage:
- Temperature Range (°C) = -65 – +125

Other:
- Series = MSD TO-5 Relay
- Brand = CII

Terms & Conditions
Privacy Policy
AODA Accessibility Policy
AODA Multi-Year Accessibility Plan

© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved

[+] Provide Website Feedback

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

2005330-1 2310537-1 936348-1 2-292161-3 2377783-2 2834055-1 3631B101LL CPF0402B37K4E1 TE50BR39J 1393431-1 1743455-2 SBCHE154R7K 917696-1 CRGCQ2010J3K3 ROX05SJ18R SMW73R0JT 1-794222-0 141991-2 175977-2 3-1393225-0 650075-000 MPT100C18RF RH73H2A40MKTN SBCHE64R7K 1-962915-1 1969656-1 3430B2F51RTDF 1903112-2 2380312-2 U5254-000005-030PA