DATASHEET

SMD ▪ B
16-219A/T2D-AQ1R2RX/3T



Features

- Package in 8mm tape on 7″ diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Mono-color type.
- Pb-free.
- The product itself will remain within RoHS compliant version.
- The maximum height is 0.25mm
- Compliance with EU REACH.
- Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm).

Description

- The 16-219A SMD LED is much smaller than lead frame type components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained.
- Besides, lightweight makes them ideal for miniature applications. etc.

Applications

- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General

Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1 www.everlight.com

Device Selection Guide

Chip Materials	Emitted Color	Resin Color
InGaN	Pure White	Yellow Diffused

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Rating	Unit
Reverse Voltage	V_R	5	V
Forward Current	I_F	10	mA
Peak Forward Current (Duty 1/10 @1KHz)	I_{FP}	20	mA
Power Dissipation	Pd	30	mW
Operating Temperature	T_{opr}	-40 ~ +85	℃
Storage Temperature	Tstg	-40 ~ +90	℃
Electrostatic Discharge	ESD_{HBM}	150	V
Soldering Temperature	T_{sol}	Reflow Soldering : 260 ℃ for 10 sec. Hand Soldering : 350 ℃ for 3 sec.	

Electro-Optical Characteristics (Ta=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	72	-----	180	mcd	I_F=2mA
Viewing Angle	$2\theta_{1/2}$	-----	130	-----	deg	
Forward Voltage	V_F	2.5	----	3.1	V	
Reverse Current	I_R	-----	-----	50	μA	V_R=5V

Note:
1. Tolerance of Luminous Intensity: ±11%
2. Tolerance of Forward Voltage: ±0.05V

Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1

Bin Range of Luminous Intensity

Bin Code	Min.	Max.	Unit	Condition
Q1	72	90	mcd	I_F =2mA
Q2	90	112		
R1	112	140		
R2	140	180		

Bin Range Of Luminous Voltage

Group	Bin Code	Min.	Max.	Unit	Condition
R	9	2.5	2.7	V	I_F =2mA
	10	2.7	2.9		
	11	2.9	3.1		

Note:
1. Tolerance of Luminous Intensity: ±11%
2. Tolerance of Forward Voltage: ±0.05V

Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1 www.everlight.com


Chromaticity Coordinates Specifications for Bin Grading

Group	Bin Code	CIE_X	CIE_Y	Condition
A	1	0.274	0.226	I_F =2mA
		0.274	0.258	
		0.294	0.286	
		0.294	0.254	
	2	0.274	0.258	
		0.274	0.291	
		0.294	0.319	
		0.294	0.286	
	3	0.294	0.254	
		0.294	0.286	
		0.314	0.315	
		0.314	0.282	
	4	0.294	0.286	
		0.294	0.319	
		0.314	0.347	
		0.314	0.315	
	5	0.314	0.282	
		0.314	0.315	
		0.334	0.343	
		0.334	0.311	
	6	0.314	0.315	
		0.314	0.347	
		0.334	0.376	
		0.334	0.343	

Notes:
1.The C.I.E. 1931 chromaticity diagram (Tolerance ±0.01).
2.The products are sensitive to static electricity and care must be fully taken when handling products.

Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1

CIE Chromaticity Diagram




Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1

Typical Electro-Optical Characteristics Curves


Spectrum Distribution

Ta=25°C




Forward Current vs.
Forward Voltage

Ta=25°C




Luminous Intensity vs.
Ambient Temperature




Luminous Intensity vs.
Forward Current

Ta=25°C




Forward Current Derating Curve




Radiation Diagram


Ta=25°C





Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1 www.everlight.com

Package Dimension










Recommend Soldering pad




Suggested pad dimension is just for reference only.
Please modify the pad dimension based on individual need.

Note: Tolerances unless mentioned ±0.1mm. Unit = mm

Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1 www.everlight.com


Moisture Resistant Packing Materials

Label Explanation



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Chromaticity Coordinates & Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number


Reel Dimensions



Note: The tolerances unless mentioned is ±0.1mm ,Unit = mm


Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1 www.everlight.com

Carrier Tape Dimensions: Loaded quantity 3000 PCS per reel



Note: The tolerances unless mentioned is ±0.1mm ,Unit = mm


Moisture Resistant Packaging



Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1 www.everlight.com


Precautions For Use

1. Over-current-proof
Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen).
2. Storage
2.1 Do not open moisture proof bag before the products are ready to use.
2.2 Before opening the package: The LEDs should be kept at 30℃ or less and 90%RH or less.
2.3 After opening the package: The LED's floor life is 1 year under 30℃ or less and 60% RH or less.
If unused LEDs remain, it should be stored in moisture proof packages.
2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.
Baking treatment : 60±5℃ for 24 hours.
3. Soldering Condition
3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.
3.3 When soldering, do not put stress on the LEDs during heating.
3.4 After soldering, do not warp the circuit board.
4.Soldering Iron
Each terminal is to go to the tip of soldering iron temperature less than 350℃ for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

5.Repairing
Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1

Application Restrictions

High reliability applications such as military/aerospace, automotive safety/security systems, and medical equipment may require different product. If you have any concerns, please contact Everlight before using this product in your application. This specification guarantees the quality and performance of the product as an individual component. Do not use this product beyond the specification described in this document.

Copyright © 2010, Everlight All Rights Reserved. Release Date : 09-Jun-2015 Issue No: DSE-0013421 Rev.1

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

EVERLIGHT:

EL817S2(C)(TU)-FG ELM3052(TA)-V IR908-7C-F(E6) IRM-3638JF 103UYD/S530-A3
11-21SURC/S530-A2/3T 19-213/Y2C-CQ2R2L/3T(CY) 27-21/GHC-YR1S2M/3C IR968-8P(X1-X4)XBY
95-21SUGC/S400-A4/TR7 ALS-PDT243-3C/L451 EL357N(A)(TA)-G ELM406A(TA)-G ITR1205ST11A/TR
PD204-6B/L3 PT334-6B IR26-21C/L110/CT ELM440A(TA)(BMS)-VG EL3083 19-21SURC/S530-A2/4T
6N137S(TA) 15-21/BHC-AP1Q2/3T 45-21UMC/404589E/TR8-T IR928-6C(6-2) EL0631(TA)
12-21SURC/S530-A2/TR8 IR383-A ITR-20001/T EL3H7(A)(TA)-G IR204C-A