8A-V8LR-SS



Where to Buy
Contact Us

View All Parts

View / Download 3D Model

DESCRIPTION	ATTRIBUTE VALUE
PRODUCT TYPE	VALVE, PROCESS NEEDLE
PRESSURE RATING	5000 PSIG (345 BAR)
CONFIGURATION	INLINE
FLOW RATE	CV = 1.23
INLET SIZE	1/2"
INLET CONNECTION	DOUBLE FERRULE COMPRESSION
OUTLET SIZE	1/2"
OUTLET CONNECTION	DOUBLE FERRULE COMPRESSION
STEM TYPE	BLUNT
STEM SEAL/PACKING	PTFE
TRIM	STAINLESS STEEL
BODY MATERIAL	STAINLESS STEEL
OPERATED	MANUAL
TEMPERATURE RATING	-65 F TO 450 F (-54 C TO 232 C)
ADDITIONAL DETAIL	
TRADE/BRAND NAME	
SYNONYM	NEEDLE VALVE

© Parker Hannifin Corp 2011

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Parker Hannifin:

1D048-8-5 6-8C3MXS RAP006.4X 1C948-16-6 1CA48-8-4 1J748-4-4 5M10C8OMXS 10C48-20-12
16N77-8-10 10-16F42EDMXS 12-8C4OMXS 1CA48-10-6 1CF48-28-16 P1A-S010SS-0050 10C4OMXS
11C77-25-12 13948-16-16 1CE48-22-12 8-12C4OMXS 8C6MXS WSV06LOMDCF 10C77-25-16
16N77-12-10 4C3MXS FM35LCF 13977-10-12 16F77-24-20 4V54D6X4-D 8JMTXS 1D048-22-12