Data Sheet

HUBER+SUHNER

Within Series Adaptor
53_N-50-0-4/133_N

Description

L-adaptor plug/jack
N plug (male) / N jack (female)



Interface standard
Series N - IEC 61169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	11 GHz		
Frequency range	DC to 2 GHz	2 to 6 GHz	6 to 8 GHz
Return loss	≥ 28 dB	≥ 20 dB	≥ 18 dB

Mechanical Data

Number of matings	500
Weight	0.0631 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Interface - N plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - N jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00013400

Ordering Information

Single package	53_N-50-0-4/133_NE

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Document: DOC-0000193983 AD / PDO L / date of publication: 17.07.2020 09:23:02 / uncontrolled copy

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

MINIBEND R-12 1399.17.0231 23000457 G032D/Nm/SMAm/1000 6620_SMA-50-2/199_NE 84118385 85201112 Minibend L-10 33_PC24-SK-50-2/199_NE 6601_PC185-50-1/199_NE 84093961 RADOX 125 0.75 MMÂ² RED PCRS_LCMX_LCMX_O421T_30.0_LL 11_TNC-50-3-116/133_NE 1399.17.0210 1399.31.0020 6806.19.A RG_196_A/U 24_SMA-50-2-15/111_NH 11MMBXEF31616MMBX/300 12012090 16_MMCX-50-2-4/111_OH 23002145 11_SMC-50-2-10/111_NE 22511964 G_03130_HT-01 12535682 G032D/BNCm/BNCm/1000 MINIBEND R-10 MINIBEND R-8