CUI DEVICES

MODEL: PP-2555TL-M | DESCRIPTION: DC POWER PLUG

FEATURES
- 7 A current rating
- 2.5 x 5.5 mm
- round cover
- twist lock tabs



RoHS

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			24		Vdc
rated input current				7	A
contact resistance	between plug and jack			30	mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	for 1 minute			500	Vac
insertion force	when mating with a standard jack	0.3		3.0	kgf
withdrawal force	when mating with a standard jack	0.3		3.0	kgf
operating temperature		-25		70	°C
operating humidity				85	%
life			5,000		cycles
flammability rating	see material table				
RoHS	yes				


SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	for maximum 1 second	380	400	420	°C

MECHANICAL DRAWING

units: mm
tolerance:
X≤1.0: ±0.1 mm
1.0<X≤6.0: ±0.2 mm
6.0<X≤12.0: ±0.3 mm
12.0<X≤25.0: ±0.4 mm
X>25.0: ±0.5 mm
unless otherwise noted

ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	insulator	PBT (UL94HB)	black
2	outer barrel	brass	nickel
3	center contact	phospor bronze	nickel
4	crimp terminal	brass	nickel
5	cover	ABS (UL94HB)	black



REVISION HISTORY

rev.	description	date
1.0	initial release	07/17/2020

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

cuidevices.com

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Same Sky:

CFM-6015V-239-292-20 SR-2540-01 TS18-5-25-SL-160-SMT-TR CEM-1212C CFM-2510B-0130-275 CMM-2718AB-38308-TR CMT-4023S-SMT-TR RCJ-014 SJ-63053B SJ1-3535NG-GR CMC-6010-42L100 CMM-4737DT-26186-TR CMP-5247TF-K CBL-UC-UC-1 CPE-253 TB003-500-P09BE TBP01R1W-508-20BE CPT-4011C-600 RDS-10S-74385-SMT-TR RDS-16S-74R-508-D TB009-508-09BE CPS-7560-110L450 CT-1205-SMT-TR RCJ-037 TBL003-254-03GR-2OR CFM-2507CF-0140-313 CFM-3010B-080-267 MPB01-1B54-SB-CAP-BK-D CMC-2742PBJ-A TBP02R2-381-12BE