
Item no.:	255-409
Product description:	PCB TERMINAL STRIP 2 SOLDER PINS / POLE 9 POLE PIN SPACING 5/5.08 MM / 0.2 IN WITH PUSH BOTTONS





Produkt kann von Bild abweichen / product may differ

Packing unit 100 4*25 pieces

Product group	4 (Printed Circuit)
Weight	10.44 g
Color	gray
No. of connection Points	9
No. of potentials	9
pole count	9
Height	14.2 mm
Height	0.559 in
Width	47.9 mm
Width	1.886 in
Depth	18.3 mm
Depth	0.72 in
Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	24 A

Pollution degree	2
Measured voltage EN	630 V

Measured shock voltage	4 kV
Current intensity EN	24 A
Connection method	CAGE CLAMP® CONNECTION
Cross section [mm²]	0.08 - 2.5 mm²
Wiring method	solid
Cross section [mm²]	0.08 - 2.5 mm²
Cross section [mm²]	0.25 - 1.5 mm²
Cross section [mm²]	0.25 - 1.5 mm²
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I

xxx-xxx/000-005	red
xxx-xxx/000-006	blue
xxx-xxx/000-008	dark gray
xxx-xxx/000-009	light gray
xxx-xxx/000-012	orange
xxx-xxx/000-017	light green

Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
255-409	ABS	04-HG469925/1-PDA	500/250	16	0,5-2,5
255-409	BV	11915/A0	500/250	16	0,08-2,5
255-409	CCA	NL6248	250	24	0,08-2,5
255-409	CSA	18677-45	300/600	15/5	28-12
255-409	DNV	E-9215	500/250	16	0,08-2,5
255-409	GL	17296-00HH	500/250	16	0,5-2,5
255-409	KEMA	2110204.02	250	16	0,5-2,5
255-409	RMR	11130002	250	16	0,5-2,5
255-409	UR	E45172	300/300	15/10	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

WAGO:

2002-1207 2086-1107 750-638/025-000 751-9301 855-3001/250-001 859-354 859-798 759-302 885-566 2102-1204 2624-3502 769-428 207-4301 260-105 2624-1312 2636-1355 2636-3108/020-000 750-1405/040-000 236-424 261-402 2787-2144 233-508 236-506 2606-3353 769-131 769-413 852-1322 2010-1205 235-502 890-503