
Materials
1. Insulator: Nylon PA46, black
2. Insulator plug: POM
3. Center terminal: C5191 phosphor bronze, 2 µm nickel plated
4. Shell: C3604 brass, 2 µm nickel plated
5. Ground terminal: C2680 brass, 2 µm nickel plated

Electrical Requirements
Dielectric strength: 1 min @ 500 Vac
Insulation resistance: 100 MΩ @ 500 Vdc
Contact resistance: 30 mΩ or less


Mechanical Requirements
Insertion force: 0.3-3 kgf
Withdrawal force: 0.3-3 kgf
Life cycle: 5000 mating cycles while maintaining 0.3 kgf min. insertion force, 0.2 kgf min. withdrawal force and less than 100 mΩ contact resistance.

Environmental Requirements
Heat test: 70 °C, relative humidity 70-85% for 96 hours while maintaining contact resistance: 100 mΩ or less, insulation resistance: 50 MΩ @ 500 Vdc, without looseness or deformation
Humidity test: 40 °C, relative humidity 90-100% for 96 hours while maintainng dielectric strength: 1 min @ 500 Vac, insulation resistance: 50 MΩ @ 500 Vdc, contact resistance: 100 mΩ or less
Salt spray test: 35 °C, relative humidity 90-95%, 5% NaCl mist for 24 hrs. Wash parts after test. Maintain mechanical requirements and a contact resistance of less than 80 mΩ.





SECTION A-A



Revision:	Date:	Description:
A	4/17/2019	Initial release

Prepared:
AG
Digitally signed by AG
Date: 2019.09.26 17:06:57 -07'00'

Verified:
AW
Digitally signed by AW
Date: 2019.09.27 08:44:43 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.3 mm
X.X: ± 0.1 mm
X.XX: ± 0.1 mm

Notes:
RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:
Connector, dc plug, 3.5x1.35x20 mm, dual solder tabs, spring contacts, nickel plated, 105 °C


TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A
Part number: 50-00620
Scale: 4:1
Sheet 1 of 2

5 4 3 2 1

Ratings
Maximum Operating Voltage: 48 Vdc
Maximum Operating Current: 5.0 A

Operating Temperature Range
-25° to 105 °C, relative humidity of 85% or less



Testing based on IEC 60512-5-2. Max current curve generated with isolated test article under controlled environmental conditions, and does not take into account external factors such as housings,mating cables, or other circuitry. Operating current curve (derated by 20% of maximum values) accounts for external factors, and manufacturing variation.

Revision:	Date:	Description:
A	4/17/2019	Initial release

Prepared:

Verified:

Dimensions are in millimeters.
Tolerances:
X: ± 0.3 mm
X.X: ± 0.1 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Connector, dc plug, 3.5x1.35x20 mm, dual solder tabs, spring contacts, nickel plated, 105 °C

TENSILITY
tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A

Part number: 50-00620

Scale: 4:1

5 4 3 2 1

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Tensility International:

10-02399 30-01029 30-01520 30-01734 053-0382R 30-01031 30-01657 10-02329 10-02959 30-01568
30-03111 30-01570 30-01739 30-01943 10-02380 30-01969 30-02978 30-00656 CA-2208 10-01096
30-01460 30-01727 30-01776 30-01991 10-01936 10-02224 10-02381 30-00873 30-00949 30-01788