
MMDT4401

DUAL NPN SMALL SIGNAL SURFACE MOUNT TRANSISTOR

Features

- Epitaxial Planar Die Construction
- Ideal for Low Power Amplification and Switching
- Ultra-Small Surface Mount Package
- **Qualified to AEC-Q101 Standards for High Reliability**
- **Lead Free/RoHS Compliant (Note 3)**
- **"Green" Device (Note 4 and 5)**



SOT-363		
Dim	**Min**	**Max**
A	0.10	0.30
B	1.15	1.35
C	2.00	2.20
D	0.65 Nominal	
F	0.30	0.40
H	1.80	2.20
J	—	0.10
K	0.90	1.00
L	0.25	0.40
M	0.10	0.25
α	0°	8°
All Dimensions in mm		

Mechanical Data

- Case: SOT-363
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Terminal Connections: See Diagram
- Marking Information: K2X – See Page 4
- Ordering & Date Code Information: See Page 4
- Weight: 0.006 grams (approximate)

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Unit
Collector-Base Voltage		V_{CBO}	60	V
Collector-Emitter Voltage		V_{CEO}	40	V
Emitter-Base Voltage		V_{EBO}	6.0	V
Collector Current - Continuous	(Note 1)	I_C	600	mA
Power Dissipation	(Note 1, 2)	P_d	200	mW
Thermal Resistance, Junction to Ambient	(Note 1)	$R_{\theta JA}$	625	°C/W
Operating and Storage Temperature Range		T_j, T_{STG}	-55 to +150	°C

Notes:
1. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at http://www.diodes.com/datasheets/ap02001.pdf.
2. Maximum combined dissipation.
3. No purposefully added lead.
4. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
5. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.

© Diodes Incorporated

Electrical Characteristics @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Min	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 6)					
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	60	—	V	I_C = 100μA, I_E = 0
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	40	—	V	I_C = 1.0mA, I_B = 0
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	6.0	—	V	I_E = 100μA, I_C = 0
Collector Cutoff Current	I_{CEX}	—	100	nA	V_{CE} = 35V, $V_{EB(OFF)}$ = 0.4V
Base Cutoff Current	I_{BL}	—	100	nA	V_{CE} = 35V, $V_{EB(OFF)}$ = 0.4V
ON CHARACTERISTICS (Note 6)					
DC Current Gain	h_{FE}	20 40 80 100 40	— — — 300 —	—	I_C = 100μA, V_{CE} = 1.0V I_C = 1.0mA, V_{CE} = 1.0V I_C = 10mA, V_{CE} = 1.0V I_C = 150mA, V_{CE} = 1.0V I_C = 500mA, V_{CE} = 2.0V
Collector-Emitter Saturation Voltage	$V_{CE(SAT)}$	—	0.40 0.75	V	I_C = 150mA, I_B = 15mA I_C = 500mA, I_B = 50mA
Base-Emitter Saturation Voltage	$V_{BE(SAT)}$	0.75 —	0.95 1.2	V	I_C = 150mA, I_B = 15mA I_C = 500mA, I_B = 50mA
SMALL SIGNAL CHARACTERISTICS					
Output Capacitance	C_{cb}	—	6.5	pF	V_{CB} = 5.0V, f = 1.0MHz, I_E = 0
Input Capacitance	C_{eb}	—	30	pF	V_{EB} = 0.5V, f = 1.0MHz, I_C = 0
Input Impedance	h_{ie}	1.0	15	kΩ	V_{CE} = 10V, I_C = 1.0mA, f = 1.0kHz
Voltage Feedback Ratio	h_{re}	0.1	8.0	x 10^{-4}	
Small Signal Current Gain	h_{fe}	40	500	—	
Output Admittance	h_{oe}	1.0	30	μS	
Current Gain-Bandwidth Product	f_T	250	—	MHz	V_{CE} = 10V, I_C = 20mA, f = 100MHz
SWITCHING CHARACTERISTICS					
Delay Time	t_d	—	15	ns	V_{CC} = 30V, I_C = 150mA, $V_{BE(off)}$ = 2.0V, I_{B1} = 15mA
Rise Time	t_r	—	20	ns	
Storage Time	t_s	—	225	ns	V_{CC} = 30V, I_C = 150mA, I_{B1} = I_{B2} = 15mA
Fall Time	t_f	—	30	ns	

Notes: 6. Short duration pulse test used to minimize self-heating effect.




Fig. 1 Max Power Dissipation vs. Ambient Temperature




Fig. 2 Typical DC Current Gain vs. Collector Current

© Diodes Incorporated




Fig. 3 Typical Capacitance




Fig. 4 Typical Collector Saturation Region




Fig. 5 Collector Emitter Saturation Voltage vs. Collector Current




Fig. 6 Base Emitter Voltage vs. Collector Current




Fig. 7 Gain Bandwidth Product vs. Collector Current


© Diodes Incorporated

Ordering Information (Note 7)

Device	Packaging	Shipping
MMDT4401-7-F	SOT-363	3000/Tape & Reel

Notes: 7. For packaging details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

Marking Information



K2X = Product Type Marking Code
YM = Date Code Marking
Y = Year ex: N = 2002
M = Month ex: 9 = September

Date Code Key

Year	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	J	K	L	M	N	P	R	S	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

© Diodes Incorporated

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

DIODES:

74AHC1G02W5-7 B190-13-F FZT605TA SBR20A300CTB-13 SMBJ30A-13-F SMCJ24A-13-F
AP7343D-18W5-7 APX809S-46SA-7 MMBTA13-7-F S1G-13-F SDT10A45P5-13 74AHCT1G02QSE-7
BC857BT-7-F BZT52C5V1T-7 PDS540-13 BZT52C3V3LP-7 ZVN4424GTA BAS40-06-7-F
SMAJ22CAQ-13-F DF04M DMG1013UWQ-13 DMTH41M8SPS-13 ZXTP718MATA AL5822W6-7
DDTD142JC-7-F SDT3A45SA-13 TLV272IM8-13 ZHCS500TA ZXMP6A13FQTA DZ9F3V6S92-7