HDC enclosures
HDC 64D SDLU 2M32G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



IP65 RoHS COMPLIANT

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.
The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.
The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.
The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.
Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Type	HDC 64D SDLU 2M32G
Order No.	1786940000
Version	HDC enclosures, Size: 8, Protection degree: IP 65, Base enclosure, End-locking clamp, lower side, high, with cover, Size of cable entries: M 32
GTIN (EAN)	4032248204182
Qty.	1 pc(s).

HDC enclosures
HDC 64D SDLU 2M32G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	144 mm	Width	98.8 mm
Height	106 mm	Mounting dimension - width	132 mm
Mounting dimension - height	45 mm	Net weight	663 g

Dimensions

Total length housing	120 mm	Width housing C	43 mm
Width base C1	57.5 mm	Height of housing B	106 mm
Height of base B1	5 mm	Hole pitch length A2	132 mm
Cable entry	w. threading		

General data

Protection class note	Protection class with secured cover: IP 65	Housing main material	diecast aluminium

Version

Internal thread	M 32	Design of housing	Base enclosure
Size	8	Design	high
Top partottom part/lid	lower part	Design of locking system	End-locking clamp, lower side
Cable entry	w. threading	Size of cable entries	M 32
Number of cable entry on top	0	Number of cable entry sideways	2
Cover	with cover	Design of cover	with cover

Classifications

ETIM 2.0	EC000437	ETIM 3.0	EC000437
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05
eClass 5.1	27-14-34-19	eClass 6.2	27-26-12-03
eClass 7.1	27-44-02-02		

Approvals

Approvals	c UL us
ROHS	Conform


Downloads

PDF	1786940000_HDC_64D_SDLU_2M32G_STP_Blatt__1.pdf
IGES	1786940000_HDC_64D_SDLU_2M32G_STP.igs
VRML	1786940000_HDC_64D_SDLU_2M32G_STP.wrl
EPLAN	1786940000.MZF
3-D model	

HDC enclosures
HDC 64D SDLU 2M32G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings



Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

WeidmÃ¼ller:

1289470000 1649300000 1804580000 1818090500 1890260000 0303620000 1124150000 1608830000
8690200000 1786450000 2535780000 024892 SAKS3 1013450000 1607520000 1609820000 1784180000
1950200000 9456650000 1779950000 1608570000 1622940000 1760040000 1127570000 1221360000
1906650000 2642470000 8951460000 1031470000 1121990000 9037380000