1-1971921-5 ✔ ACTIVE


RAST

TE Internal #: 1-1971921-5

PCB Mount Header, Vertical, Wire-to-Board, 5 Position, 5 mm [.197 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Signal, Natural

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles







Connector System: **Wire-to-Board**

Number of Positions: **5**

Number of Rows: **1**

Centerline (Pitch): **5 mm [.197 in]**

PCB Mount Orientation: **Vertical**

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Number of Positions	5
Number of Rows	1
PCB Mount Orientation	Vertical

Electrical Characteristics

Operating Voltage	250 VAC

Body Features

Primary Product Color	Natural

Contact Features

PCB Contact Termination Area Plating Material Thickness	3.8 µm[149.6 µin]
Contact Layout	Inline
Mating Tab Width	1.5 mm[.059 in]
Mating Tab Thickness	.6 mm[.024 in]
Contact Mating Area Plating Material Thickness	1.27 µm[50.8 µin]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Square
Contact Mating Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Tin
Contact Type	Tab
Contact Current Rating (Max)	2 A

Termination Features

Rectangular Termination Post & Tail Thickness	.6 mm[.024 in]
Rectangular Termination Post & Tail Width	.65 mm[.026 in]
Termination Post & Tail Length	2.9 mm[.11 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Alignment Type	Locating Posts
Mating Alignment Type	Keyed
Mating Retention	With
Mating Retention Type	Latch
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	Without

Housing Features

Housing Material	6/6 Nylon GF, Nylon
Centerline (Pitch)	5 mm[.197 in]

Dimensions

Connector Length	15.1 mm[.59 in]
Connector Height	15.5 mm[.61 in]
	.148 in

Usage Conditions

Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Operation/Application

Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	180
Packaging Method	Box, Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts




TE Part # 1-2232890-5
5P MONOPLUG 2.5 SELECTIVELY LOADED




TE Part # 1-2352002-5
5P MONOPLUG 2.5, SEL



TE Part # 8-1971817-5
5P,RAST 2.5 Tab Header,Ex- Locking, THV



TE Part # 9-1971817-5
5P,RAST 2.5 Tab Header,Ex- Locking, THV



TE Part # 4-966480-5
DUOPLUG2,5FEDLEI 7P


Customers Also Bought




TE Part #794615-4
PANEL MT DBL ROW HSG 4 POS




TE Part #293008-1
3 POS. FASTIN-FASTON CONN. TAB HOUSING R



TE Part #42037-1
RING TERMINAL 22-18 AWG TPBR




TE Part #6459633001
100G0111-0.50-9



TE Part #9040373001
100G0111-0.50-2



TE Part #1971846-2
2P, RAST 5 Tab Header, THV



TE Part #1139353001
100G0111-0.50-0



TE Part #3580590006
TRSA-1019/C/1/1

Documents

Product Drawings

3/5P,RAST 2.5 Tab Header,Ex- Locking,THV

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1971921-5_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1971921-5_A.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1-1971921-5_A.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

RAST Connector System Catalog

English

7-1773465-3_RAST2.5_Flyer

English

Product Specifications

Product Specification

English

Agency Approvals

VDE Certificate

English

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

1393431-1 141991-2 3-1393225-0 MPT100C18RF 1-962915-1 1743455-2 2377783-2 2834055-1
3430B2F51RTDF CPF0402B37K4E1 RH73H2A40MKTN SBCHE64R7K 175977-2 SBCHE154R7K
1969656-1 936348-1 1-794222-0 2-292161-3 2310537-1 2380312-2 TE50BR39J U5254-000005-030PA
2005330-1 3631B101LL 650075-000 ROX05SJ18R SMW73R0JT 1903112-2 917696-1 CRGCQ2010J3K3