

Air solenoid valve
CPV10-M1H-2OLS-2GLS-K-M7

Part number: 559646





General operating condition

Data sheet

Feature	Value
Valve function	2x2/2, open/closed, monostable
Actuation type	Electrical
Valve size	10 mm
Standard nominal flow rate	400 l/min
Pneumatic working port	M7
Operating voltage	24V DC
Operating pressure	-0.09 MPa ... 1 MPa
Operating pressure	-0.9 bar ... 10 bar
Structural design	Piston gate valve
Reset method	Pneumatic spring
Degree of protection	IP65
Nominal width	4 mm
Exhaust air function	Without flow control option
Sealing principle	Soft
Mounting position	Any
Manual override	Detenting Non-detenting
Type of control	Pilot-controlled
Pilot air supply port	External Internal
Flow direction	Non-reversible
Symbol	00991802
Lap	Overlap
Pilot pressure MPa	0.3 MPa ... 0.8 MPa
Pilot pressure	3 bar ... 8 bar
b-value	0.35
C value	1.6 l/sbar
Switching time off	17 ms
On switching time	15 ms
Duty cycle	100% in combination with holding current reduction
Electrical power consumption	0.46 W
Max. positive test pulse with 0 signal	1400 µs
Max. negative test pulse on 1 signal	700 µs
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress

Feature	Value
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Storage temperature	-20 °C ... 40 °C
Temperature of medium	-5 °C ... 50 °C
Ambient temperature	-5 °C ... 50 °C
Product weight	70 g
Type of mounting	With through-hole
Pilot air port 12/14	Common port
Pilot exhaust air port 82/84	Common port
Pneumatic connection 1	Common port with pressure separation
Pneumatic connection 11	Common port with pressure separation
Pneumatic connection 2	M7
Pneumatic port 3/5 combined	Common port
Pneumatic connection 4	M7
Note on materials	RoHS-compliant
Seals material	HNBR NBR
Housing material	Die-cast aluminum Brass POM PPS Steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

SEA-3GS-M8-S VABM-L1-10HW-G18-4-GR DSBC-32-50-D3-PPVA-N3 DSBC-63-320-D3-PPVA-N3 153034 DSBC-40-50-D3-PPSA-N3 QS-G1/8-6-I QSLV-G1/8-8 VABM-L1-14W-G14-4-GR VABM-L1-18S-G38-10 DSBC-32-40-D3-PPVA-N3 NPQP-D-R14-Q10-FD-P10 VABM-B10-20S-G14-6 DFM-63-100-P-A-KF DSBC-50-20-D3-PPSA-N3 NPQH-D-S14-Q8-P10 NPQH-T-G38-Q8-P10 QSL-12 QSLV-G1/2-12-I VABM-B10-25S-G38-4-P3 NPQH-D-Q12-Q8-P10 QS-G3/8-12 QSLV-G1/4-6 SPTW-P16R-G14-A-M12 HGL-1/8-B NPQP-D-R38-Q10-FD-P10 VABM-B10-25S-G38-6 DSBC-40-160-D3-PPSA-N3 NPQH-D-Q14-E-P10 QSL-1/4-4