
SIHA21N80AE-GE3

SiC Power MOSFET N-Channel Enhancement Mode

Features


- High Speed Switching with Low Capacitances
- High Blocking Voltage with Low On-Resistance
- Avalanche Ruggednes



TO-220F

Applications

- Solar Inverters
- Switch Mode Power Supplies
- Batterry Chargers
- High Voltage DC/DC Converters




Package Marking and Ordering Information

Ordering Part Number	Package	Brand
SIHA21N80AE-GE3	TO-220F	HXY MOSFET

Maximum Ratings (Tc = 25˚C unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions
V_{DSmax}	Drain - Source Voltage	650	V	
V_{GSmax}	Gate - Source Voltage (dynamic)	-8/+22	V	
V_{GS}	Gate - Source Voltage	-4/+18	V	
I_D	Continuous Drain Current	24	A	T_C = 25˚C
		13		T_C = 125˚C
$I_{D(pulse)}$	Pulsed Drain Current	50	A	Pulse width t_P limited by T_{jmax}
P_D	Power Dissipation	95	W	T_C = 25˚C
T_J , T_{stg}	Operating Junction and Storage Temperature	-55 to +175	˚C	
I_S	Source current(Body Diode)	24	A	T_C = 25˚C
		13		T_C = 125˚C
E_{AS}	Avalanche energy, single pulse	265	mJ	L=10mH

●Example of acceptable V_{GS} waveform



Electrical Characteristics (T_C = 25°C unless other wise specified)

Symbol	Parameter	Value			Unit	Test Condition
		min.	typ.	max.		
Static Characteristics						
$V_{(BR)DSS}$	Drain-source breakdown voltage	650	-	-	V	V_{GS}=0V, I_D=100uA
$V_{GS(th)}$	Gate threshold voltage	2	3	4	V	V_{DS}=V_{GS},I_D=2mA
I_{DSS}	Zero gate voltage drain current	- -	1 5	5 -	μA	V_{DS}=650V,V_{GS}=0V T_C=25°C T_C=175°C
I_{GSS}	Gate-source leakage current	-		100	nA	V_{GS}=18V,V_{DS}=0V
$R_{DS(on)}$	Drain-source on-state resistance	- -	110 140	140 -	mΩ	V_{GS}=18V, I_D=7A, T_J=25°C T_J=175°C
$R_{DS(on)}$	Drain-source on-state resistance	- -	145 165	200 -	mΩ	V_{GS}=15V, I_D=7A, T_J=25°C T_J=175°C
Dynamic Characteristics						
C_{iss}	Input Capacitance	-	508.0	-	pF	V_{DS} = 400V V_{GS} = 0V T_J = 25°C V_{AC}=25mV f = 1MHz
C_{oss}	Output Capacitance	-	33.0	-		
C_{rss}	Reverse Transfer Capacitance	-	3.2	-		
Q_G	Gate Total Charge		30.5	-	nC	V_{DS} = 400V V_{GS} = 0/+18V I_D = 7A I_G=10mA
Q_{gs}	Gate-Source charge	-	2.55	-		
Q_{gd}	Gate-Drain charge	-	7.9	-		
E_{ON}	Turn-On Switching Energy	-	101	-	uJ	V_{DD} = 400V V_{GS} = -4/+18V I_D = 7A R_G = 5Ω L = 1mH T_J = 25°C
E_{OFF}	Turn-Off Switching Energy	-	23	-		
$t_{d(on)}$	Turn-on delay time	-	6.5	-	ns	
t_r	Rise time	-	3.1	-		
$t_{d(off)}$	Turn-off delay time	-	29.5	-		
t_f	Fall time	-	18.5	-		
R_G	Gate resistance	-	3.0	-	Ω	V_{AC} = 25mV, f=1MHz

Body Diode Characteristics

V_{SD}	Body Diode Forward Voltage	-	4.2	-	V	V_{GS}=-4V,I_{SD}=3.5A, T_J=25°C
		-	3.8	-		V_{GS}=-4V,I_{SD}=3.5A, T_J=175°C
t_{rr}	Reverse Recovery Time	-	42.2	-	ns	V_R = 600V I_D = 7A di/dt = 1000A/μS V_{GS}= -4V T_J = 25°C
Q_{rr}	Reverse Recovery Charge	-	66	-	nC	
E_{REC}	Reverse Recovery Energy	-	14.74	-	uJ	
I_{rrm}	Peak Reverse Recovery Current	-	4.67	-	A	
t_A	Charge Time	-	20.8	-	ns	
t_B	DisCharge Time	-	21.4	-	ns	

Thermal Characteristics

Symbol	Parameter	Typ.	Unit	Test Conditions
R_{thJC}	Thermal Resistance from Junction to Case	1.55	˚C/W	
R_{thJA}	Thermal Resistance From Junction to Ambient	40		

Typical Performance

Fig 1. Output Characteristics (T_J=-55°C)




Fig 2. Output Characteristics (T_J=25°C)




Fig 3. Output Characteristics (T_J=175°C)




Fig 4: Rdson Vs Ids Characteristics




Fig 5: Rds(on) vs. Temperature




Fig 6: Transfer Characteristics




Fig 7: Body-diode Characteristics (T_J=-55°C)




Fig 8: Body-diode Characteristics (T_J=25°C)




Fig 9: Body-diode Characteristics (T_J=175°C)




Fig 10: V_{TH} Vs T_J Temperature Characteristics




Fig 11: 3rd Quadrant Characteristics(T_J=-55°C)




Fig 12: 3rd Quadrant Characteristics(T_J=25°C)




Fig 13: 3rd Quadrant Characteristics(T_J=175°C)




Fig 14: Gate Charge Characteristics




Fig 15: Drain Current vs.Case Temperature




Fig 16: Safe Operating Area




Fig 17: Capacitance Characteristics






Fig 18: Transient Thermal Impedance




Test Circuit & Waveform

Figure A. Definition of switching times



Turn-on Transient Definitions



Turn-off Transient Definitions

Figure B. Dynamic test circuit






Figure C. Definition of body diode switching characteristics




Reverse Recovery Definitions

Package Dimensions

Package TO-220F





BOTTOM VIEW

SYMBOL	DIMENSIONS		
	Min.	Nom.	Max.
A	4.60	4.70	4.80
b	0.70	0.80	0.91
b1	1.20	1.30	1.47
b2	1.10	1.20	1.30
C	0.45	0.50	0.63
D	15.80	15.87	15.97
e		2.54	
E	10.00	10.10	10.30
F	2.44	2.54	2.64
G	6.50	6.70	6.90
L	12.90	13.10	13.30
L1	3.13	3.23	3.33
Q	2.65	2.75	2.85
Q1	3.20	3.30	3.40
ΦR	3.08	3.18	3.28

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

TPSMB28A-VR AQ15C-01FTG PESDSC2FD5VU PJEC5V0M1FN2 HACPDQC5V0-HF HRCLAMP3371ZCTFT 60N06 ESD5L5.0C-HXY HCEZ36V,L3F HESDSLC3V3D3B HPTVSUC3D5VB PESDLC2FD3V3BH HLY323BC1524L HSEN3611D3 HSG3D15B3.3MA HSTS521050B331 TPSMB100CA-VR AZ4007-01H BV05C-H HAZ4007-01H HSD15C.TCT LM393DR-HXY PJSD24CW_R1 ESD5LM5.0C-HXY PESDNC2XD5VBF RLSD32A121V AZ4836-01L HESD36VD3B HSEN2411D3 PESDNC2XD5VBL