NUS1204MN

Overvoltage Protection IC with Integrated MOSFET

This device represents a new level of safety and integration by combining the NCP304 overvoltage protection circuit (OVP) with a −12 V P−Channel power MOSFET. It is specifically designed to protect sensitive electronic circuitry from overvoltage transients and power supply faults. During such hazardous events, the IC quickly disconnects the input supply from the load, thus protecting the load before any damage can occur.

The OVP IC is optimized for applications using an external AC−DC adapter or a car accessory charger to power a portable product or recharge its internal batteries. It has a nominal overvoltage threshold of 4.725 V which makes it ideal for single cell Li−Ion as well as 3/4 cell NiCD/NiMH applications.

Features

- OvervoltageTurn−Off Time of Less Than 20 μs
- Accurate Voltage Threshold of 4.725 V, Nominal
- High Accuracy Undervoltage Threshold of 2.0%
- −12 V Integrated P−Channel Power MOSFET
- Low $R_{DS(on)}$ = 75 mΩ @ −4.725 V
- Low Profile 2.0 x 2.0 mm WDFN Package Suitable for Portable Applications
- Maximum Solder Reflow Temperature @ 260°C
- This device is manufactured with a Pb−Free external lead finish only.

Benefits

- Provide Battery Protection
- Integrated Solution Offers Cost and Space Savings
- Integrated Solution Improves System Reliability

Applications

- Portable Computers and PDAs
- Cell Phones and Handheld Products
- Digital Cameras

ON Semiconductor®

http://onsemi.com

MARKING DIAGRAM




WDFN6
CASE 506AN



U2 = Specific Device Code
M = Date Code
▪ = Pb−Free Package

PIN CONNECTIONS



(Top View)

ORDERING INFORMATION

Device	Package	Shipping†
NUS1204MNT1G	WDFN6 (Pb−Free)	3000 Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2006
June, 2006 − Rev. 1

Publication Order Number:
NUS1204MN/D




Figure 1. Simplified Schematic

PIN FUNCTION DESCRIPTIONS

Pin #	Symbol	Pin Description
1	GATE	Gate pin of the P−Channel Power MOSFET
2	OUT	This signal drives the gate of a P−channel Power MOSFET. It is controlled by the voltage level on the IN pin. When an overvoltage event is detected, the OUT pin is driven to within 1.0 V of V_{IN} in less than 20 μsec provided that gate and stray capacitance is less than 12 nF.
3, 7	GND	Circuit Ground
4	IN	This pin senses an external voltage point. If the voltage on this input rises above the overvoltage threshold (V_{TH}), the OUT pin will be driven to within 1.0 V of V_{IN}, thus disconnecting the P−Channel Power MOSFET. The nominal threshold level is 4.725 V and this threshold level can be increased with the addition of an external resistor between the IN pin and the adapter.
5	SOURCE	Source pin of the P−Channel Power MOSFET
6, 8	DRAIN	Drain pin of the P−Channel Power MOSFET

OVERVOLTAGE PROTECTION CIRCUIT TRUTH TABLE

IN	OUT
$<V_{th}$	GND
$>V_{th}$	V_{IN}

MAXIMUM RATINGS (T_A = 25°C unless otherwise stated)

Rating	Pin	Symbol	Min	Max	Unit
OUT Voltage to GND	2	V_O	−0.3	12	V
Input Pin Voltage to GND	4	V_{input}	−0.3	12	V
Maximum Power Dissipation (Note 1)	−	P_D	−	0.96	W
Thermal Resistance Junction−to−Air (Note 1) OVP IC P−Channel FET	−	$R_{\theta JA}$	−	130 130	°C/W
Junction Temperature	−	T_J	−	150	°C
Operating Ambient Temperature	−	T_A	−40	85	°C
Storage Temperature Range	−	T_{stg}	−65	150	°C
ESD Performance (HBM) (Note 2)	2,3,4	−	2.5	−	kV
Drain−to−Source Voltage		V_{DSS}		−12	V
Gate−to−Source Voltage		V_{GS}	−8	8	V
Continuous Drain Current, Steady State, T_A = 25°C (Note 1)		I_D		−0.6	A

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Surface−mounted on FR4 board using 1 inch sq pad size (Cu area = 1.127 in sq [1 oz] including traces).
2. Human body model (HBM): MIL STD 883C Method 3015−7, (R = 1500 Ω, C = 100 pF, F = 3 pulses delay 1 s).

ELECTRICAL CHARACTERISTICS (T_A= 25°C, Vcc = 6.0 V, unless otherwise specified)

Characteristic	Symbol	Min	Typ	Max	Unit
Input Threshold (Pin 4, V_{in} Increasing)	V_{TH}	4.630	4.725	4.820	V
Input Threshold Hysteresis (Pin 4, V_{in} Decreasing)	V_{HYS}	0.135	0.225	0.315	V
Supply Current (Pin 4) (V_{in} = 4.34 V) (V_{in} = 6.5 V)	I_{in}	 − −	 − −	 3.0 3.9	μA
Minimum Operating Voltage (Pin 4) (Note 3) (T_A = 25°C) (T_A = −40°C to 85°C)	$V_{in(min)}$	 − −	 0.55 0.65	 0.70 0.80	V
Output Voltage High (V_{in} = 8.0 V; I_{Source} = 1.0 mA) Output Voltage High (V_{in} = 8.0 V; I_{Source} = 0.25 mA) Output Voltage High (V_{in} = 8.0 V; I_{Source} = 0 mA)	V_{oh}	V_{in}−1.0 V_{in}−0.25 V_{in}−0.1	−	−	V
Output Voltage Low (Input < 4.5 V; I_{Sink} = 0 mA; CNTRL = 0 V)	V_{ol}	−	−	0.1	V
Propagation Delay Input to Output Complementary Output NCP304 Series Output Transition, High to Low Output Transition, Low to High	 t_{pHL} t_{pLH}	 − −	 10 21	 − 60	μs

3. Guaranteed by design.

P−CHANNEL MOSFET (T_A= 25°C, unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Units
Drain to Source On Resistance V_{GS} = −4.5 V, I_D = 600 mA V_{GS} = −4.5 V, I_D = 1.0 A	$R_{DS(on)}$		 75 75	 100 100	mΩ
Zero Gate Voltage Drain Current V_{GS} = −4.5 V, V_{GS} = 0 V, V_{DS} = −10 V	I_{DSS}			 −1.0	μA
Turn On Delay (Note 4) V_{GS} = −4.5 V	t_{on}		 5.5		ns
Turn Off Delay (Note 4) V_{GS} = −4.5 V	t_{off}		 20		ns
Input Capacitance V_{GS} = 0 V, f = 1.0 MHz, V_{DS} = −10 V	C_{in}		 531		pF
Gate to Source Leakage Current V_{GS} = 8.0 V, V_{DS} = 0 V	I_{GSS}		 ±10		nA
Drain to Source Breakdown Voltage V_{GS} = 0 V, I_D = −250 μA	$V_{(BR)DSS}$	 −12			V
Gate Threshold Voltage V_{GS} = V_{DS}, I_D = −250 μA	$V_{(GS)th}$	 −0.4	 −0.7	 −1.0	V


4. Switching characteristics are independent of operating junction temperature.

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS


ON Semiconductor®

WDFN6 2x2, 0.65P
CASE 506AN
ISSUE G


DATE 22 AUG 2013




SCALE 4:1




TOP VIEW




SIDE VIEW



DETAIL B
OPTIONAL CONSTRUCTIONS



DETAIL A
OPTIONAL CONSTRUCTIONS




BOTTOM VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 mm FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS	
DIM	MIN	MAX
A	0.70	0.80
A1	0.00	0.05
A3	0.20 REF	
b	0.25	0.35
D	2.00 BSC	
D2	0.57	0.77
E	2.00 BSC	
E2	0.90	1.10
e	0.65 BSC	
F	0.95 BSC	
K	0.25 REF	
L	0.20	0.30
L1	---	0.10


GENERIC MARKING DIAGRAM*



XX = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

SOLDERMASK DEFINED MOUNTING FOOTPRINT



DIMENSIONS: MILLIMETERS

STYLE 1:
PIN 1. SOURCE 1
2. GATE 1
3. DRAIN 2
4. SOURCE 2
5. GATE 2
6. DRAIN 1

STYLE 2:
PIN 1. ANODE
2. N/C
3. DRAIN
4. SOURCE
5. GATE
6. CATHODE

STYLE 3:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. DRAIN 2
5. GATE 2
6. DRAIN 1

DOCUMENT NUMBER:	**98AON20861D**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**WDFN6 2X2, 0.65P**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

ON Semiconductor Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ON Semiconductor:

FSL538HFLYGEVB MUR860G FCB070N65S3 NVMJS0D8N04CLTWG MUR2020RG NTPF110N65S3HF ECH8654-TL-H NTMFS0D55N03CGT1G NFVA22512NP2T NXH300B100H4Q2F2SG SMDA15CDR2G NCV8537MN180R2G NCP3237MNTXG NC7SZ08M5X NTBS2D7N06M7 1N5357BG FOD4116 FGH4L40T120LQD NTMFS015N15MC NFAM0512L5BT FFSB2065BDN-F085 MMBD2835LT1G FGH4L50T65SQD FAN7382MX NCV78M05BDTRKG NTMFS1D3N04XMT1G SZMMSZ4689T3G NXH010P90MNF1PTG NSR0520V2T1G NTMFS5C670NLT3G