Dual N-Channel Advanced Power MOSFET

Features

- V_{DS}= 60V, I_D= 5 A
  $R_{DS(ON)}$ < 30 mΩ @ V_{GS} = 10V
  $R_{DS(ON)}$ < 36 mΩ @ V_{GS} = 4.5V

General Features

- Advanced Trench Technology
- Provide Excellent RDS(ON) and Low Gate Charge
- Lead Free and Green Available

100% UIS TESTED!
100% ΔVds TESTED!

RoHS



SOP-8 (Dual)



Pin Assignment



Schematic diagram

Absolute Maximum Ratings (T_A=25℃ unless otherwise specified)

Symbol	Parameter		Max.	Units
V_{DSS}	Drain-Source Voltage		60	V
V_{GSS}	Gate-Source Voltage		±20	V
I_D	Continuous Drain Current	T_A= 25℃	5	A
		T_A= 100℃	3.3	A
I_{DM}	Pulsed Drain Current note1		20	A
EAS	Single Pulsed Avalanche Energy note2		20	mJ
P_D	Power Dissipation	T_A= 25℃	1.74	W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient		72	℃/W
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to +150	℃

Electrical Characteristics (T_J=25℃ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristics						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250μA	60	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=60V, V_{GS} = 0V,	-	-	1.0	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS}=0V, V_{GS} = ±20V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250μA	1.0		2.5	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note3	V_{GS}=10V, I_D=5A	-		30	mΩ
		V_{GS}=4.5V, I_D=3A	-		36	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}=25V, V_{GS}=0V, f=1.0MHz	-	853	-	pF
C_{oss}	Output Capacitance		-	60	-	pF
C_{rss}	Reverse Transfer Capacitance		-	29	-	pF
Q_g	Total Gate Charge	V_{DD}=30V, I_D=2.5A, V_{GS}=10V	-	20	-	nC
Q_{gs}	Gate-Source Charge		-	3	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	4.5	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DD}=30V, I_D=5A, R_{GEN}=1.8Ω, V_{GS}=10V	-	6	-	ns
t_r	Turn-on Rise Time		-	6	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	19	-	ns
t_f	Turn-off Fall Time		-	2.5	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	5	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	20	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS}=0V, I_S=5A	-	-	1.2	V
trr	Body Diode Reverse Recovery Time	I_F=5A, dI/dt=100A/μs	-	13	-	ns
Qrr	Body Diode Reverse Recovery Charge		-	9	-	nC

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. EAS condition :Starting T_J=25℃,V_{DD}=30V,V_{GS}=10V,L=0.5mH,Rg=25Ω,I_{AS}=9A

3. Pulse Test: Pulse Width≤300μs, Duty Cycle≤0.5%

Typical Performance Characteristics

Figure 1: Output Characteristics



Figure 2: Typical Transfer Characteristics



Figure 3: On-resistance vs. Drain Current



Figure 4: Body Diode Characteristics



Figure 5: Gate Charge Characteristics



Figure 6: Capacitance Characteristics



Figure 7: Normalized Breakdown Voltage vs. Junction Temperature



Figure 8: Normalized on Resistance vs. Junction Temperature



Figure 9: Maximum Safe Operating Area



Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature



Figure 11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



Test Circuit



Figure1:Gate Charge Test Circuit & Waveform



Figure 2: Resistive Switching Test Circuit & Waveforms



Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms