

Representative Image

Catalog No. TY528MX

Description: CBL TIE 50LB 14.2PO UV BLACK

UPC No 786210805146

Home > Wire & Cable Management > Ty-Rap > Cable ties

Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 360.68mm (14.2 Inches), Width of 4.83mm (0.19 Inches), Tensile Strength Rating of 222 Newtons (50 pounds)

Descriptors

Category	Cable ties
Type	High Performance
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.

Specifications

Material	Nylon/Polyamide 6.6
Color	Black
Lock Mechanism	Stainless Steel Barb
Tensile Strength	50 pounds , 222 newtons

Classifications

Brand Name	Ty-Rap

Dimensions

Width	0.19 in , 4.9 mm
Length	14.2 in , 361 mm
Thickness	0.05 in , 1.3 mm
Bundle Diameter	0.12 to 4.02 in , 3 to 102 mm

Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ABB:

1SL1204A00 ESB16-20N-06 SH203-C16 CR-M4SFB ESB25-22N-03 1SVR730700R2200 7TAG009520R0070 ESB25-40N-03 ESB63-20N-01 GSH201 AC-C16/0.03 S202-B6 AX09-30-01-80*220-230V 50Hz/230-240V60Hz ESB25-13N-04 MS132-1.0 CR-S024VADC1CRS ESB63-40N-05 LW205 SH203-C25 APTS020A0X3-SRZ CT-MKC.31 ESB63-22N-06 WT115A 2CCA880212R0001 ESB40-30N-07 LCN75 WT540 CP1-10G-11 OXP6X360 SE201-C10 SU201M-K16