2320935-2 ✔ ACTIVE


AMP | AMPSEAL 16

TE Internal #: 2320935-2

Housing for Female Terminals, Wire-to-Device / Wire-to-Wire, 6 Position, 4.5 mm [.177 in] Centerline, Sealable, Gray, Wire & Cable, Power, AMPSEAL 16

View on TE.com >

Connectors > Automotive Connectors > Automotive Housings > AMPSEAL 16 Housings







Connector System: **Wire-to-Device, Wire-to-Wire**

Number of Positions: **6**

Connector & Housing Type: **Housing for Female Terminals**

Centerline (Pitch): **4.5 mm [.177 in]**

Sealable: **Yes**

All AMPSEAL 16 Housings (224)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Device, Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing

Configuration Features

Blank Cavity Position	0
Number of Positions	6
Number of Rows	2

Electrical Characteristics

Operating Voltage	250 VAC

Body Features

Cable Exit Angle	180°
Primary Product Color	Gray
Connector & Keying Code	B

Contact Features

Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.5 mm[.06 in]
Contact Current Rating (Max)	13 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF15
Centerline (Pitch)	4.5 mm[.177 in]

Dimensions

Connector Height	31 mm[1.22 in]
Product Width	36.7 mm[1.44 in]
Product Length	25.3 mm[.966 in]
Row-to-Row Spacing	5.3 mm[.209 in]
Compatible Insulation Diameter Range	1.27 – 3.3 mm[.05 – .131 in]
Wire Size	.52 – 2.08 mm^2

Usage Conditions

Operating Temperature (Max)	150 °C[302 °F]
Operating Temperature Range	-40 – 150 °C[-40 – 302 °F]

Operation/Application

Circuit Application	Power

Industry Standards

Degree of Protection	IP67
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	22
Packaging Method	Tube

Other

Serviceable	Yes
Connector Position Assurance Capable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) **Article Safe Usage Statements:** Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 776363-1
SEALING PLUG, SZ 16 CAVITY




TE Part # CAT-AM7801-T273
AMPSEAL 16 CONTACTS



TE Part # 776441-1
AS 16, EXTRACTION TOOL



TE Part # 2320929-2
AS16,CAP ASSY,HT,06P,E SEAL,CODE B




TE Part # 2272179-4
AMPSEAL 16 PERIPHERAL SEAL 6P - SERVICE

Also in the Series | AMPSEAL 16



Automotive Connector Caps & Covers (3)



Automotive Connector Locks & Position Assurance(2)



Automotive Housings(244)



Automotive Terminals(35)



Connector Backshells(84)



Connector Seals & Cavity Plugs(4)



Data Connectivity Headers(2)



Data Connectivity Housings(3)




Other Automotive Connector Accessories(11)

Customers Also Bought



TE Part #9-1393211-3
T92S11D22-12




TE Part #1-2308346-7
FULL METAL HOODS SIZE 5 - 7 (RAW)



TE Part #2320933-1
AMPSEAL 16 Housings



TE Part #1924579-3
PIN CONTACT WIRE TO WIRE NICKE



TE Part #1670144-2
MCON 1.2 CB REC SRC AU

Documents

Product Drawings

AS16,PLUG ASSY,HT,06P,E SEAL,CODE B

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2320935-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2320935-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2320935-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

1-962915-1 1393431-1 2380312-2 3430B2F51RTDF 3631B101LL CRGCQ2010J3K3 SBCHE154R7K
175977-2 2834055-1 SBCHE64R7K U5254-000005-030PA 650075-000 936348-1 CPF0402B37K4E1
2005330-1 2377783-2 SMW73R0JT 2-292161-3 2310537-1 3-1393225-0 TE50BR39J 1-794222-0
917696-1 1743455-2 MPT100C18RF RH73H2A40MKTN ROX05SJ18R 141991-2 1903112-2 1969656-1