Datasheet for part number CA3102R16-11SF183

Our Catalog Part Number: CA3102R16-11S-F183
Our Global Manufacturing Part Number: 121001-0654 R
Brand: Cannon Product Category: Circular Product Line: MIL-DTL 5015 Series I Series: MIL-C-5015

Product Datasheet	
Thread	Connector with threaded coupling
Shell Style	Box mounting receptacle
Gender	Socket
Shell Size	16
Contact Arrangement	16-11
Number of contacts	2 contacts size 12
Contact Type	Solder Cup
Contact Plating	Hard silver
Shielding	no
Contact Rating at +20 °C (68 °F) (Size 25/12)	41 A
Contact Resistance (Size 25/12)	3 mΩ
Operating Voltage	In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.
Insulator Resistance	Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 MΩ
Test Voltage	1600 Vrms
Air and Creepage Paths (Min)	1,1 mm
Ambient Temperature	Standard insulator material -55°/+125°C (-67/257°F)
Safety Provisions	IP67 acc. to DIN 40 050 (1 bar pressure after 12 hrs)
Salt Spray Resistance	500 hours salt spray resistant
Mating Cycles	500 min
Sep. Force per Contact (Size 25/12)	1,5 N
Gage	For infos on Gage please see catalog VG95234, part 1
Coupling Torque	Closing: 5,5 Nm max / Opening: 0,46 Nm min
Contact Retention (Size 25/12)	55 N
Shell Material	Aluminium alloy
Shell Plating	Olive drab chromate coating over cadmium plating
Insulator and Gromet Material	Neoprene
Contact Material	Copper alloy
Harnessing Info: Contact Cross-Section	See assembly instruction
Harnessing Info: Insulator Diameter	See assembly instruction
Wire Stripping (Size 25/12)	6,2 mm
General Info	*All tests in accordance with VG95319 and/or if applicable with VG95210*

Specifications and dimensions subject to change.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

ITT:

XLR531 MS3106E2222P CA06COME14SA7S-44 MS3106F16S-8S CA3101F14S-A7PA206 CA3108E24-10PBF80 MS3102E12S3P CA3102E16S-1PWBF80A176 CA3102R18-10PY VG95234B1-28-11SN 192900-0030 CA3102E16S-1SWBF80A176 CA3102E18-10PYBF80 CA3102R16S-4P CB12-12SG KPT02E-12-3S KPT06J-14-12P MS3101R10SL-4S CA3102E16S-5SB CA3102R14S-6S CA3102R18-22SF80 CA3108R20-23SB KPT02E83AP 1929900460 CA08COM-F14S-2S CA3100F18-10PB CA3102E16-10PXBF80 CA3102E24A24PB01A176 KPT04-12-3S VG95234B1-22-22PN