2-1586038-4 ✔ ACTIVE

VAL-U-LOK


TE Internal #: 2-1586038-4

Header, Plug, Wire-to-Board, 24 Position, 4.2 mm [.165 in] Centerline, Printed Circuit Board, UL 94V-0, Rectangular Power Connectors

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors




Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Board**

Number of Positions: **24**

Centerline (Pitch): **4.2 mm [.165 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	24
PCB Mount Orientation	Vertical
Number of Power Positions	24
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC

Contact Features

Contact Layout	Inline, Matrix

Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	9 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	2.03 µm[80 µin]

Termination Features

Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without
Mating Retention Type	Latch
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	4.2 mm[.165 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

Compatible Insulation Diameter (Max)	2.39 mm[2.39 in]
Connector Height	12.8 mm[.504 in]
PCB Thickness (Recommended)	.06 mm[1.6 in]
Product Width	9.75 mm[.384 in]
Product Length	51.6 mm[2.031 in]
Compatible Insulation Diameter Range	1.2 – 3.1 mm[.047 – .122 in]
Row-to-Row Spacing	4.2 mm[.165 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Operation/Application

Circuit Application	Power

Identification Marking

Circuit Identification Feature	With

Industry Standards

UL Rating	Recognized
Compatible With Agency/Standards Products	UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	105
Packaging Method	Box & Tray, Tray

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts



TE Part # 2-1586019-4
24P RCPT VAL-U-LOK V0



TE Part # 2-1969613-4
24P PM PLUG VAL-U-LOK V0



TE Part # 2-1969612-4
24P FH PLUG VAL-U-LOK V0


Customers Also Bought



TE Part #DTF15-12PD
DEUTSCH DT Headers



TE Part #6437288-3
SUPER SEAL 60POS CAP ASSY H AU



TE Part #5100143-1
2MM H.M. TYPE "A" PIN ASSY.




TE Part #5-104069-3
80 sys 50 hdr drra shrd sn



TE Part #644753-4
04P MTA156 HDR ASSY RN STR F/L



TE Part #643410-1
08P UMNL PIN HDR ASSY POL 94VO



TE Part #794956-2
VAL-U-LOK SKT BR AU 22-18AWG



TE Part #3-1393303-4
V23134B1052C642-EV-CBOX



TE Part #3-2176455-9
CPF 0402 274K 0.1% 25ppm 1K RL

Documents

Product Drawings

24P VRT HDR VAL-U-LOK V0

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1586038-4_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1586038-4_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1586038-4_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

917696-1 936348-1 MPT100C18RF U5254-000005-030PA CRGCQ2010J3K3 RH73H2A40MKTN
1-962915-1 1969656-1 3430B2F51RTDF 650075-000 ROX05SJ18R 1393431-1 141991-2 2380312-2
SBCHE64R7K 3631B101LL SBCHE154R7K 1903112-2 2834055-1 3-1393225-0 CPF0402B37K4E1
SMW73R0JT TE50BR39J 1-794222-0 2-292161-3 2377783-2 1743455-2 175977-2 2005330-1 2310537-1