
FEATURES

* Current transfer ratio
  (CTR : MIN. 40% at I_F = 5mA, V_{CE} = 5V)
* High isolation voltage between input and output
  (V_{iso} = 5,000Vrms)
* High collector-emitter voltage
  (V_{CEO} : 300V)
* Dual-in-line package :
  LTV-851 : 1-channel type
* Wide lead spacing package :
  LTV-851M : 1-channel type
* Surface mounting package :
  LTV-851S : 1-channel type
* Tape and reel packaging :
  LTV-851S-TA, LTV-851S-TA1
* Safety approval
  UL, FIMKO, CSA, VDE* approved
  ("*" Requires "V" ordering option)
* RoHS compliance


OUTLINE DIMENSIONS

LTV-851 :


TYPE I (INK MARK)



TYPE II (LASER MARK)




LTV-851M :



*1. Year date code.
*2. 2-digit work week.
*3. Factory identification mark shall be marked
(W: China-CZ, X: China-TJ, Y : Thailand).

OUTLINE DIMENSIONS


LTV-851S :




*1. Year date code.
*2. 2-digit work week.
*3. Factory identification mark shall be marked
(W: China-CZ, X: China-TJ, Y : Thailand).

TAPING DIMENSIONS

LTV-851S-TA :



LTV-851S-TA1 :



Description	Symbol	Dimensions in mm (inches)
Tape wide	W	16 ± 0.3 (.63)
Pitch of sprocket holes	P_0	4 ± 0.1 (.15)
Distance of compartment	F P_2	7.5 ± 0.1 (.295) 2 ± 0.1 (.079)
Distance of compartment to compartment	P_1	12 ± 0.1 (.472)

ABSOLUTE MAXIMUM RATING

(Ta = 25°C)

PARAMETER		SYMBOL	RATING	UNIT
INPUT	Forward Current	I_F	50	mA
	Reverse Voltage	V_R	6	V
	Power Dissipation	P	70	mW
OUTPUT	Collector - Emitter Voltage	V_{CEO}	300	V
	Emitter - Collector Voltage	V_{ECO}	6	V
	Collector Current	I_C	50	mA
	Collector Power Dissipation	P_C	150	mW
Total Power Dissipation		P_{tot}	200	mW
*1 Isolation Voltage		V_{iso}	5,000	Vrms
Operating Temperature		T_{opr}	-25 ~ +100	°C
Storage Temperature		T_{stg}	-55 ~ +125	°C
*2 Soldering Temperature		T_{sol}	260	°C

*1. AC For 1 Minute, R.H. = 40 ~ 60%

Isolation voltage shall be measured using the following method.

(1) Short between anode and cathode on the primary side and between collector and emitter on the secondary side.

(2) The isolation voltage tester with zero-cross circuit shall be used.

(3) The waveform of applied voltage shall be a sine wave.

*2. For 10 Seconds

ELECTRICAL - OPTICAL CHARACTERISTICS

(Ta = 25°C)

PARAMETER		SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
INPUT	Forward Voltage	V_F	—	1.2	1.4	V	I_F=20mA
	Reverse Current	I_R	—	—	10	μA	V_R=4V
	Terminal Capacitance	C_t	—	30	250	pF	V=0, f=1KHz
OUTPUT	Collector Dark Current	I_{CEO}	—	—	1	μA	V_{CE}=200V, I_F=0
	Collector-Emitter Breakdown Voltage	BV_{CEO}	300	—	—	V	I_C=0.1mA I_F=0
	Emitter-Collector Breakdown Voltage	BV_{ECO}	6	—	—	V	I_E=10μA I_F=0
TRANSFER CHARACTERISTICS	Collector Current	I_C	2	—	—	mA	I_F=5mA V_{CE}=5V
	*1 Current Transfer Ratio	CTR	40	—	—	%	
	Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	—	0.1	0.3	V	I_F=20mA I_C=1mA
	Isolation Resistance	R_{iso}	5×10^{10}	1×10^{11}	—	Ω	DC500V 40 ~ 60% R.H.
	Floating Capacitance	C_f	—	0.6	1	pF	V=0, f=1MHz
	Cut-Off Frequency	f_c	—	50	—	kHz	V_{CE}=5V, I_C=2mA R_L=100Ω, -3dB
	Response Time (Rise)	t_r	—	4	10	μs	V_{CE}=2V, I_C=2mA R_L=100Ω
	Response Time (Fall)	t_f	—	5	12	μs	

*1 $CTR = \frac{I_C}{I_F} \times 100\%$

CHARACTERISTICS CURVES

Fig.1 Forward Current vs. Ambient Temperature




Fig.2 Collector Power Dissipation vs. Ambient Temperature




Fig.3 Collector-emitter saturation Voltage vs. Forward current




Fig.4 Forward Current vs. Forward Voltage




Fig.5 Current Transfer Ratio vs. Forward Current





Fig.6 Collector Current vs. Collector-emitter Voltage



CHARACTERISTICS CURVES

Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.8 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.9 Collector Dark Current vs. Temperature




Fig.10 Response Time vs. Load Resistance







Fig.11 Frequency Response



Test Circuit for Response Time



Test Circuit for Frequency Response



TEMPERATURE PROFILE OF SOLDERING REFLOW

- Lite-On is continually improving the quality, reliability, function or design and Lite-On reserves the right to make changes without further notices.

- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.

- For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.

- When requiring a device for any " specific" application, please contact our sales in advice.

- If there are any questions about the contents of this publication, please contact us at your convenience.

- The contents described herein are subject to change without prior notice.

- Immerge unit's body in solder paste is not recommended.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

LITE-ON:

LTL-307P LTST-E682KGKSWT LTST-G563EGBW LTST-S220KRKT LTST-S321KRKT LTSTC195KGJRKT
LTV-155E LTV-847 LTL-307E LTR-S320-DB-L LTST-C190KYKT LTST-C193KRKT-5A LTSTC150KRKT
LTV-814S-TA1-A LTW-C193TS5 LTV-715F LTV814S-TA1 LTL2R3KEK LTST-C150TGKT LTST-C230GKT
LTV-171G-TP-G LTW-010SCIB-SR LTST-C150YKT LTST-S270KRKT LTSTS220TBKT LTW-150TK
LTST-C193KGKT-5A LTST-C930EKT LTST-G683RGBW LTSTC155KGJRKT