
Force Guided Relay SR6 A/B/C/V

- **6 pole relay with force guided contacts according to EN61810-3 (formerly EN50205)**
- **Reinforced insulation between all contacts**

Typical applications
Emergency shut-off, press control, machine control, elevator and escalator control, safety relays



Approvals

VDE Cert. No. 128935, UL E214025, TUV 968/EL 350,
CCC 2020970303000302
Technical data of approved types on request

Contact Data

Contact arrangement	3 form A + 3 form B contacts 3 NO + 3 NC, 4 form A + 2 form B contacts 4 NO + 2 NC, 5 form A + 1 form B contacts 5 NO + 1 NC	
Rated voltage	250VAC	
Max. switching voltage	400VAC	
Rated current	8A	
Contact material	$AgSnO_2$, $AgSnO_2$ + 0.2µm Au	
Contact style	single contact, force guided type A according to EN61810-3 (formerly EN50205)	
Min. recommended contact load Initial contact resistance	5V, 10mA ≤100mΩ at 1A, 24VDC ≤20Ω at 10mA, 5VDC	
Frequency of operation, with/without load	$6/150min^{-1}$	
Contact ratings		
IEC60947-5-1		
on 1 form A (NO) contact	AC15 - 250V/5A	6.050
	DC13 - 24V/6A	6.050
UL 61810-1 (former UL 508)		
on 1 form A (NO) contact	8A, 250VAC, 70°C	
	General purpose	6.000
	B00/R300	6.000
Mechanical endurance	$10x10^6$ operations	

Coil Data

Coil voltage range	5 to 110VDC
Max. coil power	1200mW or 800mW

Coil versions, DC-coil 800mW

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%	Rated coil power mW
K12	12	9	1.2	180	800
K15	15	11.3	1.5	281	801
K18	18	13.5	1.8	405	800
K21	21	16	2.1	551	800
K24	24	18	2.4	720	800
K36	36	27	3.6	1620	800
K48	48	36	4.8	2880[1)]	800
L10	110	82.5	11.0	15130[1)]	800


1) Coil resistance ±12%.
All figures are given for coil without pre-energization, at ambient temperature +23°C.

Coil versions, DC-coil 1200mW


Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%[1)]	Rated coil power mW
005	5	3.8	0.5	20.8	1200
006	6	4.5	0.6	30.0	1200
009	9	6.8	0.9	67.5	1200
012	12	9	1.2	120	1200
018	18	13.5	1.8	270	1200
021	21	16	2.1	368	1200
024	24	18	2.4	480	1200
036	36	27	3.6	1080	1200
040	40	30	4.0	1333	1200
048	48	36	4.8	1920	1200
060	60	45	6.0	3000[1)]	1200
110	110	83	11.0	10080[1)]	1200

1) Coil resistance ±12%.
All figures are given for coil without pre-energization, at ambient temperature +23°C.


Max. DC load breaking capacity




Electrical endurance 1200mW version



Coil operating range DC



Coil operating range DC



04-2022, Rev. 0222
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Force Guided Relay SR6 A/B/C/V (Continued)


Insulation Data	
Initial dielectric strength	
between open contacts	1500V_{rms}
between contact and coil	4000V_{rms}
between adjacent contacts	3000V_{rms}
Clearance/creepage	
between open contacts	microdisconnection
between contact and coil	≥5.5/5.5mm
between adjacent contacts	≥5.5/5.5mm
Insulation to IEC EN 62477 (former EN 50178), type of insulation	
between contact and coil	reinforced
between adjacent contacts	reinforced

Other Data	
Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customersupport/rohssupportcenter	
Ambient temperature	-25 to 70°C
Category of environmental Protection	
IEC 61 810	RTIII[1)]
1) Washing not recommended. The user is encouraged to check suitability for washing under actual conditions.	
Weight	30g
Resistance to soldering heat THT	
IEC 60068-2-20	260°C/5s
Packaging/unit	tube/10 pcs.


For more detailed information see product specification 2158003

Dimensions

SR6 A/B/C




SR6 V




PCB layout / terminal assignment

Bottom view


3 form A + 3 form B, 3 NO + 3 NC versions
SR6 A



4 form A + 2 form B, 4 NO + 2 NC versions
SR6 B





5 form A + 1 form B, 5 NO + 1 NC versions
SR6 C



4 form A + 2 form B, 4 NO + 2 NC versions
SR6 V

The design of the SR6 V allows clearance/creepage of 5.5 mm on the PCB.





04-2022, Rev. 0222
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Force Guided Relay SR6 A/B/C/V (Continued)

Product code structure — Typical product code: **SR6 A 4 012**

Type
- **SR6** Relay with force guided contacts SR6

Contact arrangement
- **A** 3 form A + 3 form B contacts (3 NO + 3 NC)
- **B** 4 form A + 2 form B contacts (4 NO + 2 NC)
- **V** 4 form A + 2 form B contacts (4 NO + 2 NC) (crossed pin layout)
- **C** 5 form A + 1 form B contacts (5 NO + 1 NC)

Contact material
- **4** $AgSnO_2$ for 1200mW version
- **6** $AgSnO_2$ + 0.2µm Au for 800mW version

Coil

Coil code: please refer to coil versions table (e.g. 024=24VDC)

Other types on request

Product code	Type	Cont. arrangement	Cont. material	Coil	Coil Power	Alt. Description	Part Number
SR6A4005	6 pole	3 form A + 3 form B,	$AgSnO_2$	5VDC	1200mW	V23050-A1005-A533	8-1415017-1
SR6A4012	relay with	3 NO + 3 NC		12VDC		V23050-A1012-A533	1-1415015-1
SR6A4021	force guided	contacts		21VDC		V23050-A1021-A533	3-1415018-1
SR6A4024	contacts			24VDC		V23050-A1024-A533	1415015-1
SR6A4048				48VDC		V23050-A1048-A533	6-1415018-1
SR6A4060				60VDC		V23050-A1060-A533	7-1415018-1
SR6A4110				110VDC		V23050-A1110-A533	9-1415018-1
SR6A6K12			$AgSnO_2$ + Au	12VDC	800mW		6-1415537-1
SR6A6K18				18VDC			6-1415537-3
SR6A6K24				24VDC			6-1415537-5
SR6B4005		4 form A + 2 form B,	$AgSnO_2$	5VDC	1200mW	V23050-A1005-A542	1393260-1
SR6B4006		4 NO + 2 NC		6VDC		V23050-A1006-A542	1393260-2
SR6B4012		contacts		12VDC		V23050-A1012-A542	1393260-4
SR6B4018				18VDC		V23050-A1018-A542	1393260-5
SR6B4021				21VDC		V23050-A1021-A542	1393260-6
SR6B4024				24VDC		V23050-A1024-A542	1393260-7
SR6B4040				40VDC		V23050-A1040-A542	1393260-9
SR6B4048				48VDC		V23050-A1048-A542	1-1393260-0
SR6B4060				60VDC		V23050-A1060-A542	1-1393260-1
SR6B4085				85VDC		V23050-A1085-A542	1-1393260-2
SR6B4110				110VDC		V23050-A1110-A542	1-1393260-3
SR6B6K12			$AgSnO_2$ + Au	12VDC	800mW		7-1415537-6
SR6B6K15				15VDC			7-1415537-7
SR6B6K18				18VDC			7-1415537-8
SR6B6K21				21VDC			7-1415537-9
SR6B6K24				24VDC			8-1415537-0
SR6C4012		5 form A + 1 form B,	$AgSnO_2$	12VDC	1200mW	V23050-A1012-A551	1-1415017-1
SR6C4024		5 NO + 1 NC		24VDC		V23050-A1024-A551	1415017-1
SR6C4048		contacts		48VDC		V23050-A1048-A551	2-1415019-1
SR6C4060				60VDC		V23050-A1060-A551	3-1415019-1
SR6C4110				110VDC		V23050-A1110-A551	5-1415019-1
SR6C6K24			$AgSnO_2$ + Au	24VDC	800mW		9-1415537-4
SR6V6K12		4 form A + 2 form B,		12VDC			3-1415542-5
SR6V6K15		4 NO + 2 NC		15VDC			2-1415543-2
SR6V6K18		contacts		18VDC			3-1415543-3
SR6V6K21		(crossed pin layout)		21VDC			4-1415542-4
SR6V6K24				24VDC			5-1415539-2

04-2022, Rev. 0222
www.te.com
© 2015 Tyco Electronics Corporation,
a TE Connectivity Ltd. company

Datasheets and product specification according to IEC 61810-1 and to be used only together with the 'Definitions' section.

Datasheets and product data is subject to the terms of the disclaimer and all chapters of the 'Definitions' section, available at http://relays.te.com/definitions

Datasheets, product data, 'Definitions' section, application notes and all specifications are subject to change.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

CPF0402B37K4E1 RH73H2A40MKTN ROX05SJ18R 1743455-2 2005330-1 3430B2F51RTDF 650075-000
CRGCQ2010J3K3 141991-2 3-1393225-0 U5254-000005-030PA 1903112-2 175977-2 2-292161-3
TE50BR39J 936348-1 MPT100C18RF SBCHE64R7K 1-794222-0 1-962915-1 2377783-2 917696-1
SMW73R0JT 1393431-1 1969656-1 2310537-1 SBCHE154R7K 2380312-2 2834055-1 3631B101LL