Data Sheet

HUBER+SUHNER

Within Series Adaptor
34_BNC-50-0-1/133_N

Description

Bulkhead adaptor jack/jack
BNC jack (female) / BNC jack (female)



Interface standard
Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
VSWR	DC - 4 GHz ≤ 1.08 + 0.1 f (GHz)
Frequency range	DC to 1.5 GHz
Return loss	≥ 34 dB

Mechanical Data

Number of matings	500
Weight	0.0171 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Interface - BNC jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	

Interface - BNC jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	

Related Documents

Catalogue drawing	DCA-00013669
Mounting hole	DOU-00008751

Ordering Information

Single package	34_BNC-50-0-1/133_NE

Within Series Adaptor
34_BNC-50-0-1/133_N

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

24_SMA-50-2-15/111_NH 6601_PC185-50-1/199_NE G032D/Nm/SMAm/1000 11MMBXEF31616MMBX/300
11_SMC-50-2-10/111_NE MINIBEND R-8 PCRS_LCMX_LCMX_O421T_30.0_LL
RADOX 125 0.75 MMÂ² RED 12535682 23002145 33_PC24-SK-50-2/199_NE 84093961 MINIBEND R-10
MINIBEND R-12 RG_196_A/U 1399.17.0231 16_MMCX-50-2-4/111_OH 1399.17.0210
11_TNC-50-3-116/133_NE 1399.31.0020 22511964 G032D/BNCm/BNCm/1000 G_03130_HT-01 23000457
6620_SMA-50-2/199_NE 85201112 Minibend L-10 12012090 6806.19.A 84118385