Detailed Specifications

Frame Width:	20[mm]
Frame Height:	69[mm]
Frame Depth:	69[mm]
Nominal Voltage:	24[V]
Max. Air Flow:	7.1[CFM]
Max. Static Pressure:	0.6[In H2O]
Speed:	4100[min-1]
Noise:	33[dB]
Life Expectancy:	25 degree C 70,000 Hours[L10]
Bearing Type:	Ball Bearing
Operating Voltage Lower:	12[V]
Operating Voltage Upper:	26.4[V]
Nominal Current:	0.13[A]
Input Power:	3.12[W]
Mass:	55[g]
Status:	Active

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

NMB Technologies:

06020SA-24L-AA-00 06025SA-24T-AA-D0 07530GA-12K-AA-00 12038VE-24R-GT-E0
DDRI1438HHRA5P24LY121 11938MB-B3L-EA-00 DDL-310HA1P25LO1 09225PB-A1L-EA-00
11938FB-A1N-EA-00 DDLF-1260ZZP24LY121 06076EA-12S-E6-0C 11938MB-B0N-EA-00
17250VE-24R-GT-00 R200A4-051-D0550 03828DA-12R-AU-00 04020VA-24N-AA-00 11938MA-24P-GA-00
R172H1-051-D0760 08025VE-12P-GT-D0 08028GS-12N-AA-00 11925PB-B3L-EA-00 06025DE-12R-CU-06
07530GA-24M-AA-00 17250VE-48R-GT-00 DDRIF814ZZMTRA5P24LY121 04020VA-24P-AL-00
06025VG-12Q-ZT-A0 06030PB-A1L-AA-00 09225SA-24M-EA-D0 15050VA-24N-EA-00